

EXCELAM-Q1600 RS COLD


SUPER COLD LAMINATING RESULTS

- Ideal for laminating posters, ink-jet prints, leaflets and maps with superb results.
- This laminator also offers professional mounting up to 13mm GMP Lamifoam (Foamboard).
- Variable speed and pressure adjust handle.
- All our cold machines now incorporate heavy duty motors giving a running speed of 5 m/min.



FEATURES

- High speed laminating of up to 5m/minute.
- Strengthened main motor for better drive torque and durability.
- Rewinder connected to the powerful main motor.
- Top rewriter for releasing liner.
- Easy to use for outer rewriter tension control.



FILM ADAPTOR / DUAL 3"



SAFETY SENSOR



POWER SWITCH



BACK TRIMMER

Model Name	Excelam-Q1600 RS COLD
Dimensions (WxLxH)	1840 x 750 x 1200mm
Max. Laminating Speed	5m/min
Max. Laminating Width	1600mm
Laminating Films	75mic ~ 500mic
Substrate Thickness	80g/m ² ~ 350g/m ²
Max. Thickness Mount	13mm
Power Requirements	220 ~ 240V, 50/60Hz
Power Consumption	100W, 0.4A
Speed Control	Knob and Volume
Film Core	77mm / Dual
Type of Main Motor	DC-Geared Motor
Type of Rewinder Motor	Link to Main Motor

GMP reserves the right to change specifications without prior notice.