

EXCELAM II SERIES

HOT ROLLER LAMINATOR FOR THE PROFESSIONAL ENVIRONMENT

- The Excelam II Series are ideal for schools, offices or professional use.
- Ideal for laminating posters, ink jet prints, leaflets and maps with guaranteed professional results.
- Superb laminating results on a wide range of standard laminating film.



FEATURES

- Installed safety device (slide latch).
- Speed and temperature control.
- Hot and cold lamination.
- Mounting up to 5mm thick foamboard.
- 8-bit microprocessor controlled pre-set functions.
- Pre-set functions include hot and cold settings, preheat, temperature measurement and reverse with override for full speed and temperature control.
- Accurate temperature measurement with use of infrared sensor.
- Transparent roller cover is easily detached with use of magnets.
- Paper guide on feed table.
- Tension control on film mandrel.
- Variable pressure control.
- Lami-table (optional).



**THE EXCELAM
II-655Q WITH
LAMI-TABLE
(OPTIONAL)**

Model Name	EXCELAM II-355Q	EXCELAM II-655Q
Dimensions (WxLxH)	585 x 450 x 285mm	885 x 450 x 285mm
Max. Laminating Speed	1.3m/min	1.3m/min
Max. Laminating Width	355mm	655mm
Laminating Films	25mic ~ 500mic	25mic ~ 500mic
Substrate Thickness	80g/m ² ~ 350g/m ²	80g/m ² ~ 350g/m ²
Thickness Mount	5mm	5mm
Front Roller Diameter	55mm	55mm
Rear Roller Diameter	30mm	30mm
Power Requirements	220 ~ 240V, 50/60Hz	220 ~ 240V, 50/60Hz
Power Consumption	1400W, 6.0A	1700W, 7.0A
Warm-up Time	10 minutes	10 minutes
Heating System	Hot Roller Internal Infrared Heater	Hot Roller Internal Infrared Heater
Operating Temperature	Max. 150°C	Max. 150°C
Speed Control	Key Pad	Key Pad
Temperature Control	Key Pad	Key Pad
Pressure Control	Manual (6 steps)	Manual (6 steps)
Film Core	14 - 25WH	14 - 25WH
Cooling System	AC Fan	Blower
Main Motor	DC W-Geared Motor / 36V70	DC W-Geared Motor / 36V70
Stand	No	Optional

GMP reserves the right to change specifications without prior notice.