

# MYJOY SERIES

## PHOTOGRAPHIC POUCH LAMINATOR

- Ideal for all standard laminating applications.
- Temperature guide table provided on laminator casing for ease of use.
- Handles paper sizes from credit cards to A3.
- Water-proof and tamper-proof results every time.



### FEATURES

- Temperature control.
- Quality hot and cold lamination.
- Compact and portable, simple to use.
- User-friendly operation for quick, quality results.
- Super quick warm-up time and stable temperature control with special Ruthenox heater.

### APPLICATIONS

- ID cards
- Business cards
- Luggage tags
- Membership cards
- Certificates
- Posters
- Documents

Model Name	MyJoy-4	MyJoy-9	MyJoy-12
Laminating Speed	420mm / min	50Hz: 460mm / min, 60Hz: 560mm / min	50Hz: 460mm / min, 60Hz: 560mm / min
Laminating Width	100mm	230mm	320mm
Laminating Films	75mic ~ 250mic	75mic ~ 250mic	75mic ~ 250mic
Substrate Thickness	80g/m <sup>2</sup> ~ 250g/m <sup>2</sup>	80g/m <sup>2</sup> ~ 250g/m <sup>2</sup>	80g/m <sup>2</sup> ~ 250g/m <sup>2</sup>
Power Requirements	220 ~ 240V, 50/60Hz	220 ~ 240V, 50/60Hz	220 ~ 240V, 50/60Hz
Power Consumption	240W, 1.0A	470W, 2.0A	520W, 2.1A
Warm-up Time	1 minute	1 minute	1 minute
Heating System	Ruthenox Heater	Ruthenox Heater	Ruthenox Heater
Operating Temperature	150°C Max.	150°C Max.	150°C Max.
Speed Control	Fixed	Fixed	Fixed
Temperature Control	Knob and volume	Knob and volume	Knob and volume
Dimensions (WxLxH)	300 x 185 x 95mm	425 x 185 x 95mm	500 x 185 x 95mm
Type of Main Motor	Synchronous Motor-S	Synchronous Motor-S	Synchronous Motor-S

GMP reserves the right to change specifications without prior notice.

## 4 SIMPLE STEPS TO LAMINATION

1



### STEP 1

Press the power switch "On".

2



### STEP 2

Set machine to suitable laminating temperature.

The indicator lamp activates when ready.

3



### STEP 3

Insert document into pouch laminator.

4



### STEP 4

Within seconds you have a laminated document.