

# SURELAM PRO 500D

## TRADE ROLL LAMINATOR

- Maximum laminating speed of 7m/min
- Pre-set functions 8-bit micro-processor controlled
- Patented top and bottom film alignment system
- LCD display helps to eliminate operation errors
- Decurling device for single-side lamination
- Heat shoe and hot roller combination
- Increased film capacity
- Turbo cooling system
- Feeding guide on feed table
- Safety shield



### FEATURES

- Pressure control.
- Unique film tracking system for easy film alignment.
- Cross cutter and turbo power cooling system.
- Side lays on feed table.
- Opening heat shoes for easy roller cleaning and larger roll film capacity.

Model Name	SURELAM PRO 500D
Dimensions (WxLxH)	760 x 615 x 460mm
Max. Laminating Speed	7m/min
Max. Laminating Width	500mm
Laminating Films	25mic ~ 500mic
Substrate Thickness	80g/m <sup>2</sup> ~ 350g/m <sup>2</sup>
Front Roller Diameter	50mm
Rear Roller Diameter	50mm
Power Requirements	220 ~ 240V, 50/60Hz, 12A
Power Consumption	3000W, 12.6A
Warm-up Time	7 minutes
Heating System	Heat Shoe and Infrared Heater
Laminating Temperature	Max. 150°C
Temperature Control	Key Pad
Speed Control	Key Pad
Pressure Adjustment	Manual (5 steps)
Film Core	19 - 58WH
Cooling System	Blower
Type of Main Motor	DC W-Geared Motor

GMP reserves the right to change specifications without prior notice.