# VLCAM100 Ultra-HD ePTZ



The Vivolink VLCAM100 is a high-definition ePTZ camera specifically designed for small meetings, classrooms and distance learning. It supports USB 3.0 and is plug-and-play with just one USB cable. Thanks to its built-in TV mount, it is easy to install on the TV or on the screen. With the 120° wide viewing angle and 3 x magnification, attendees appear clear. In addition, it has a built-in microphone and is an excellent choice and best suited for distance learning or videoconferencing.

#### **Key Features**

- Supports USB 3.0 / 2.0 plug & play
- With Auto Framing function
- 4K image sensor with 8.28 Megapixel
- Output resolution up to 3264 x 2448
- Panoramic 120° viewing angle
- 4x digital zoom
- ePTZ, Remote control
- Built-in microphone

Compatible with all popular applications and cloud systems:













GoTo Meeting Blueleans







## USB 3.0 Plug & Play

The VLCAM100 uses standard UVC drivers. There is no need to install special USB drivers. USB 3.0 is 10 times faster than the USB

2.0 standard and it features low latency and non-compress output.



## Excellent 4K Image

The VLCAM100 has a professional 8.28 megapixel image sensor that features high resolution, and Vivid color reproduction and presents an excellent image quality even under insufficient liaht conditions.



#### Ultra-View Angle

The VLCAM100 has a panoramic ultra-wide 120° viewing angle that helps users achieve a wider viewing area



#### With Auto Framing

The VLCAM100 auto framing can auto zoom on people when enter or leave people during the video conferencing



#### Easy control

The VLCAM100 easy control like Pan, Tilt, Zoom and settings by IR remote controller. Supports Windows, Mac OS, Android system.



#### 10 Preset Positions

The VLCAM100 has 10 preset via remote control for pan, tilt, zoom, focus, and white balance modes for more effective and efficient video recording.



## Adaptive Microphone Design

The VLCAM100 with two built-in microphones is a best fit for distance learning or video conferencing. Pick up distance up to 3 meter.



# Easy Install on TV Screen

The USB 3.0 cable has a 3 meter design allowing the VLCAM100 to install for different display size.

## **Product Specifications**

Sensor	1/2.5" 8.28 MP CMOS	ePTZ	Support
Video Output	Main stream: 3840×2160@30fps 1920×1080P@30fps/25fps 1280×720P@30fps/25fps, etc. Sub-stream: 1280×720P@30fps/25fps 640×480P@30fps/25fps 320×172P@30fps/25fps	Preset Positions	IR: 10 Sets USB: 255 sets
		Video Format	YUV / MJPEG/ H.264/ H.265
		Video Output (HD) Interface	USB 3.0 (USB 2.0 Compatible
		Microphone	Build in 2 microphones
Auto Framing Function	Yes	White Balance	Manual / Auto
View Angle	126° (Diagonal), 120° (Horizontal)	Exposure Control	Auto
Minimum Object Distance	50 cm	Brightness Control	Yes
Remote Control	Yes	brightness control	163
Operation Systems		Audio Over USB3.0	Yes
	Windows, MacOS™, Linux	Focus System	Fixed Focus
Digital Zoom	4x	Noise Reduction	2D & 3D DNR
Camera Control Interface	IR remote control / USB	Size	222mm×93.25mm×56.5mm
Driver	UVC / UAC	Weight	Main Unit : 0.53kg

# I/O Connections

Front Rear





#### Accessories

#### Ceiling/wall mount





## **Monitor shelf**



#### **USB3.0** Cable extension



5 m 10 m 20 m 30 m PROUSB3AAF5 PROUSB3AAF10 PROUSB3AAF20 PROUSB3AAF30