



1D & 2D



Megapixel



Coiled
cable



Dual
Interface



IP42



1.5m
drop



EasySet



Warranty
5 Years



**HR32 Marlin
Coded**
Handheld Scanners

Features

Megapixel camera.

The HR32 Marlin Coded is a barcode scanning powerhouse. No matter what type of barcode is presented, the megapixel camera allows users to scan 1D and 2D barcodes, including very small and high resolution codes, with impressive speed and ease.

Durable Construction.

Users in retail setting will enjoy the strong exterior and drop resistance up to 1.5m. With an IP42 rating, the device is protected against water and dust.

Superior ergonomics.

The HR32 Marlin Coded is the ideal solution for scan-intensive use in retail and logistics. The scanner fits

comfortably in any user's hand, reducing the fatigue of long-time operation.

All-round scanning capability.

Whether you need a barcode scanner that can be used on paper or displayed on a screen, you'll be set with the HR32 Marlin Coded. The device delivers unmatched scanning performance for both conventional and emerging applications.

Offered with a coiled cable.

Foldable smart stand available.

It is possible to order a foldable smart stand as an accessory or as a set with the scanner.

Suggested industries



Finance



Healthcare



Hospitality



Postal



Retail

HR32 Marlin Coded Technical specifications

Performance

| | |
|------------------------------------|--|
| Image Sensor | CMOS 1280 x 800 |
| Processor | 1GHz, X1500 |
| Illumination | Red LED (625±10 nm) / White LED |
| Aiming | Green LED |
| Depth of Field EAN 13 (13mil) | 45-510mm |
| Depth of Field Code 39 (5mil) | 75-220mm |
| Depth of Field PDF417 (6.67mil) | 70-215mm |
| Depth of Field Data Matrix (10mil) | 50-220mm |
| Depth of Field QR (15mil) | 20-330mm |
| Minimal Print Contrast | 25% |
| Scan Angle Roll | 360° |
| Scan Angle Pitch | ±55° |
| Scan Angle Skew | ±55° |
| Field of View Horizontal | 39° |
| Field of View Vertical | 24° |
| Scan Modes | Trigger (Level, Pulse), Sense, Continuous Mode |
| Scan Rate | 60 frames per second |

Data Capture

| | |
|----|--|
| 1D | All major 1D symbologies, including EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey. |
| 2D | All major 2D symbologies, including PDF417, QR Code, Data Matrix, Aztec, Maxicode. |

Physical

| | |
|--------------------------|-----------------------------------|
| Dimensions (mm) | 113.5(W) × 73.3(D) × 159.0(H) |
| Weight | 162g |
| Material | PC, ABS |
| Buttons | Trigger |
| Interfaces | RS-232, USB |
| Notifications | Beep, LED indicator |
| Input Voltage | 5VDC ± 5% |
| Current @ 5VDC Operating | 238.2mA (typical), 260.5mA (max.) |
| Current @ 5VDC Standby | 71.3mA |
| Power Consumption | 1289.6mW (typical) |
| Power Supply Input | DC5V, 1.5A |
| Power Supply Output | AC100~240V, 50~60Hz |

Environmental

| | |
|---------------|--------------------------------|
| Ambient Light | 0 ~ 100000 lux (natural light) |
|---------------|--------------------------------|

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved

HR32 Marlin Coded Technical specifications

| | |
|--------------------------------|--|
| Operating Temperature | -20°C to 60°C (-4°F to 140°F) |
| Storage Temperature | -40°C to 70°C (-40°F to 158°F) |
| Humidity | 5%~95% (non-condensing) |
| Electro Static Discharge (ESD) | ±15 kV (air discharge), ±8 kV (direct discharge) |
| Drop | 1.5m |
| IP Rating | IP42 |

Accessories

| | |
|----------|---|
| Standard | USB Cable, Adapter, Stand standard in a set (also available seperately) |
| Optional | RS232 Cable, USB Cable |

Software

| | |
|---------------------|---------|
| Configuration Tools | EasySet |
|---------------------|---------|

Certifications

| | |
|----------|-----------------------------|
| Hardware | CE, FCC, RoHS, IEC62471, KC |
|----------|-----------------------------|

Warranty

| | |
|----------|---------|
| Standard | 5 years |
|----------|---------|

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved