



**NQire 750
Stingray**
Micro Kiosks

Features

Android OS.

The NQire 750 Stingray uses Android 7.1 OS. With this reliable operating system comes a feature-rich environment for stable apps that are tried and tested. Android 7.1 is an excellent match for the applications most suited to the NQire 750. Particularly when operating within four walls, fitting the NQire 750's PoE (Power over Ethernet) connectivity.

Free MDM included.

The NQire 750 Stingray comes with the option of running Newland's free MDM solution: Ndevor. As a result, the Micro Kiosk lends itself perfectly for the coordination of multiple units. Managing information from a shared database, organizing applications and settings across many individual units, as well as low-touch assistance in troubleshooting can all be managed from a centralized location.

Mount anywhere.

The NQire 750 Stingray's slimline and lightweight design is suitable for mounting on any shelf edge. Options to mount the NQire series range from shelf to wall and free-standing. Its classic Vesa75 configuration also ensures existing industry standard, 3rd party solutions are compatible.

Snappy Megapixel Scanning.

Barcode data capture is at the heart of Newland's Micro Kiosks and so the

NQire 750 is fitted with their own Megapixel scanning technology. This maintains high standards for the scanning of both large and small 1D & 2D barcodes. The Micro Kiosk further includes optimal settings for reading barcodes presented on smartphone and tablet screens. With the scanner set at a 20° angle, it matches the ergonomics of how the user presents codes for scanning.

Multi-purpose display.

The sharp, full-colour screen on the Stingray is perfect for running animations and live recorded videos when not actively being used. With onboard memory, expanded memory and online options, the choice of content to display is virtually limitless.

Endless communication possibilities.

With WiFi, Ethernet, Powered Ethernet (PoE) and Bluetooth, this Micro Kiosk offers a variety of standard communication possibilities. Additionally, optional 4G means that the NQire 750 Stingray can communicate and be communicated with, no matter the circumstance. Adding to that the wide variety of data capture options, such as integrated barcode reading, MSR, NFC and low frequency RFID, application possibilities are endless.

Modules can only be ordered pre-mounted to the connector on the left or right side.

Suggested industries



Events



Hospitality



Manufacturing



Public Sector



Retail



NQuire 750 Stingray Technical specifications

Performance

Image Sensor	1280 x 800 CMOS
Operating System	Android 7.1
Processor	1.5GHz octa-core 64-bit
Memory RAM	2GB DDR3
Memory Flash	8GB Emmc
Memory Storage Expansion (max.)	Micro SD card up to 128GB
Illumination	White LED
Aiming	650nm laser diode
Depth of Field EAN 13 (13mil)	70-600mm
Depth of Field Code 39 (5mil)	120-280mm
Depth of Field PDF417 (6.67mil)	110-230mm
Depth of Field Data Matrix (10mil)	110-260mm
Depth of Field QR (15mil)	55-400mm
Minimal Print Contrast	25%
Scan Angle Roll	360°
Scan Angle Pitch	±50°
Scan Angle Skew	±50°
Field of View Horizontal	42°
Field of View Vertical	28°

Data Capture

1D	All major 1D symbologies, including Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, GS1 Composite Code, Matrix 2 of 5, Code11, Industrial 25, Standard 25, Plessey, MSI-Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Chinese Sensible Code, Aztec Code, Maxicode, MicroPDF417*.

Physical

Dimensions (mm)	195(H)x138.5(W)x25(D)mm
VESA standard	Complies with the standard VESA 75 bracket, enabling easy mounting on shelves and walls
Display	7" 1280x800 IPS display
Touch Panel	5-point capacitive touch panel
Interfaces	USB 2.0 host, type A port, micro USB 2.0 type B, OTG, programmable GPIO (2 in - 2 out)
Input Voltage	DC12V, 2A
Power Consumption	12W (MAX)
Power Supply Input	AC110 ~ 220V, 50~60Hz
Power Supply Output	DC12V, 2A
Sensors	Gravity Sensor
Power over Ethernet	802.3af

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved

NQuire 750 Stingray Technical specifications

Audio	82dB dual-channel stereo sound speaker
-------	--

Expansion Slot	Micro SD up to 128GB
----------------	----------------------

Camera	Front pixel 5 million pixels (FixedFocus)
--------	---

Environmental

Operating Temperature	-10°C to 50°C (14°F to 122°F)
-----------------------	-------------------------------

Storage Temperature	-20°C to 60°C (-4°F to 140°F)
---------------------	-------------------------------

Humidity	5% to 90% (non-condensing)
----------	----------------------------

Wireless

WLAN RADIO	IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5Ghz (optional)
------------	--

WPAN RADIO	Bluetooth 4.0 LE, EDR + BLE (optional)
------------	--

RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FeliCa (optional)
------	---

Accessories

Optional	4G module, Magnetic card reader module, NFC reader module, RFID reader module, Desktop stand Vesa75, Adjustable wall mount bracket Vesa75 (all modules can be mounted on the left or right)
----------	---

Software

MDM (certified)	Ndevor, SOTI
-----------------	--------------

Terminal Emulation (compatible)	StayLinked, Airwatch
---------------------------------	----------------------

Configuration Tools	Ndevor
---------------------	--------

Certifications

Hardware	CE, RoHS, IEC/EN 62471
----------	------------------------

Warranty

Standard	2 years
----------	---------

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved