



Fall Protection

General Fluid Resistance Guide: 3M™ DBI-SALA® Quick Wrap Tape II

General Fluid Resistance

Fluid	Fluid Resistance Rating
Ammonia	3
Biobutanol	3
Biodiesel	2
Brake Fluid	5
Diesel Fuel	1
Ethanol	4
Ethylene Glycol	5
Gasoline	1
Grease	3
Propylene Glycol	5
Shock Absorber Fluid	3
Sulfuric Acid (20% dilution)	2
Transmission Fluid	3
Water (Contaminated)	5

Rating Key

1	Very Poor
2	Poor
3	Fair
4	Good
5	Excellent

3M cannot guarantee the suitability of this material in all applications.

The guide is based on mild contamination on or around tape surface only.

When excessive exposure is expected with a fluid rated less than 3, additional exterior protection is recommended, such as 3M™ DBI-SALA® Heat Shrink.

i IMPORTANT NOTE

The above properties are published as a guide only. They should not be used for specifications without further testing for a specific application.

3M Personal Safety Division

3M Fall Protection Business
3833 SALA Way
Red Wing, MN 55066

Technical Service: 800-328-6146
3M.com/FallProtection

3M PSD products are
for occupational use only.

© 3M 2017. All rights reserved.
3M, DBI-SALA, and Protecta are trademarks
of 3M Company and affiliates.
Used under license in Canada.
All other trademarks are property
of their respective owners.
Please recycle. Release 1, October 2017