

Ausführungen | Versions ST-1100

Bezeichnung Description	E	A	Farben / Colours			Artikel-Nr. Item-No.
	Eingang Inlet	Ausgang Outlet	Gehäuse Housing	Hebel Trigger	Klinke Lock	
ST-1100	G3/8 IG G3/8 female	G1/4 IG G1/4 female	schwarz black	schwarz black	schwarz black	20 1100 500
ST-1100 NPT	3/8" NPT IG 3/8" NPT female	1/4" NPT IG 1/4" NPT female	schwarz black	schwarz black	schwarz black	20 1100 510
ST-1100 Weep	3/8" NPT IG 3/8" NPT female	1/4" NPT IG 1/4" NPT female	schwarz black	schwarz black	blau blue	20 1100 525
ST-1100 Drehglk. Weep ST-1100 Swivel Weep	G3/8 IG Drehglk. G3/8 female Swiv.	G1/4 IG G1/4 female	schwarz black	schwarz black	blau blue	20 1100 530
ST-1100 Drehgelenk ST-1100 Swivel	G3/8 IG Drehglk. G3/8 female Swiv.	G1/4 IG G1/4 female	schwarz black	schwarz black	schwarz black	20 1100 540

Technische Daten | Specification

Druck Pressure	210 bar		3050 psi
Temperatur Temperature	150 °C		300 °F
Durchfluss Flow rate	25 l/min		6,6 US gal/min
Druckverlust	19 bar	(bei 30 l/min)	
Pressure drop	280 psi	(at 8 US gal/min)	
Öffnungskraft, Haltekraft Triggering force, hold. force			
100 bar 1450 psi:	35 N,		20 N
150 bar 2170 psi:	50 N,		25 N
200 bar 2900 psi:	70 N,		30 N
Gewicht Weight	0,43 kg		
	0,48 kg	mit Swivel	

