



ENVIRO
BUILD

NBS DATA

HYPERION

DECKING

PIIONEER

DECKING BOARD

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	50 x 50mm, 100 x 50mm/ 150 x 50mm/ 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/ end clips, 72 x 12mm fascia boards, 54 x 40mm corner trims
CoefficientOfExpansion	0.032 mm/m/°C - (-30°C to +30°C)
ColourOptions	Oak, Walnut, Granite, Stone, White Ash
FlexuralModulus	4188 MPa
FlexuralStrength	33.58 MPa
ImpactStrength	86 J/m Izod Unnotched
LengthOptions	2.2 or 4.0 m
Profile	Reversible Grooved or Wood Grain
Recyclability	100%
RecycledContent	90% (60% wood fibre and 30% HDPE)
SectionSize	21 x 145 mm
SlipPotentialValue	Low potential for slip; Wet: 40 Dry: 52
TensileStrength	25.6 MPa (ASTM D638-10)
WaterAbsorption	1.04%
AcousticRating	n/a
Combustible	TRUE
Finish	Deep grooves or Wood grain
FireRating	Cfl – s1 (EN 13501-1)
FlammabilityRating	n/a
FragilityRating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	Pioneer Reversible Decking
TotalThickness	21 mm
HasAntiStaticSurface	FALSE
HasNonSkidSurface	TRUE
TechnicalContact	info@envirobuild.com





ENVIRO
BUILD

NBS DATA

HYPERION

DECKING

FRONTIER

DECKING BOARD

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	50 x 50mm, 100 x 50mm/ 150 x 50mm/ 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/ end clips, 140 x 12mm fascia boards
CoefficientOfExpansion	0.032 mm/m/°C - (-30°C to +30°C)
ColourOptions	Slate, Iroko, Teak, Marble
FlexuralModulus	4423 MPa
FlexuralStrength	40.5 MPa
LengthOptions	4.0 m
Profile	Reversible Grooved or Wood Grain
Recyclability	100%
RecycledContent	90% (60% wood fibre and 30% HDPE)
SectionSize	22 x 143 mm
SlipPotentialValue	Moderate to Low potential for slip; Wet: 29, Dry: 49
WaterAbsorption	0.88%
AcousticRating	n/a
Combustible	TRUE
Finish	Deep grooves or Wood grain
FlammabilityRating	n/a
FragilityRating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	Frontier Reversible Decking
TotalThickness	22 mm
HasAntiStaticSurface	FALSE
HasNonSkidSurface	TRUE
TechnicalContact	info@envirobuild.com



NBS DATA

HYPERION

 DECKING

PIONEER

FASCIA BOARD

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	50 x 50mm, 100 x 50mm/ 150 x 50mm/ 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/ end clips, 54 x 40mm corner trims
CoefficientOfExpansion	0.032 mm/m/°C - (-30°C to +30°C)
ColourOptions	Oak, Walnut, Granite, Stone, White Ash
ImpactStrength	86 J/m Izod Unnotched
LengthOptions	2.2 m
Profile	Uniform Plank
Recyclability	100%
RecycledContent	90% (60% wood fibre and 30% HDPE)
SectionSize	72 x 12 mm
WaterAbsorption	1.04%
AcousticRating	n/a
Combustible	TRUE
Finish	Brushed flat grain surface
FlammabilityRating	n/a
FragilityRating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	Pioneer Fascia Board
TotalThickness	12 mm
HasAntiStaticSurface	FALSE
HasNonSkidSurface	TRUE
TechnicalContact	info@envirobuild.com

HYPERION

 DECKING

PIONEER

CORNER NOSING TRIM

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	50 x 50mm, 100 x 50mm/ 150 x 50mm/ 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/ end clips, 72 x 12mm fascia board
CoefficientOfExpansion	0.032 mm/m/°C - (-30°C to +30°C)
ColourOptions	Oak, Walnut, Granite, Stone, White Ash
ImpactStrength	86 J/m Izod Unnotched
LengthOptions	2.2 m
Profile	Uniform L Trim
Recyclability	100%
RecycledContent	90% (60% wood fibre and 30% HDPE)
SectionSize	54 x 40 mm
WaterAbsorption	1.04%
AcousticRating	n/a
Combustible	TRUE
Finish	Brushed flat grain surface
FlammabilityRating	n/a
FragilityRating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	Pioneer Fascia Board
TotalThickness	5 mm
HasAntiStaticSurface	FALSE
HasNonSkidSurface	TRUE
TechnicalContact	info@envirobuild.com

NBS DATA

HYPERION

 DECKING

FRONTIER

FASCIA BOARD

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	50 x 50mm, 100 x 50mm/ 150 x 50mm/ 100 x 100mm plastic joists, 3/6mm gap hidden fasteners, start/ end clips, 54 x 40mm corner trims
CoefficientOfExpansion	0.032 mm/m/°C - (-30°C to +30°C)
ColourOptions	Slate, Iroko, Teak, Marble
ImpactStrength	86 J/m Izod Unnotched
LengthOptions	2.2 m
Profile	Uniform Plank
Recyclability	100%
RecycledContent	90% (60% wood fibre and 30% HDPE)
SectionSize	140 x 12 mm
WaterAbsorption	0.88%
AcousticRating	n/a
Combustible	TRUE
Finish	Brushed flat grain surface
FlammabilityRating	n/a
FragilityRating	n/a
Material	Wood (FSC 100%) polymer composite (WPC)
Reference	Frontier Fascia Board
TotalThickness	12 mm
HasAntiStaticSurface	FALSE
HasNonSkidSurface	TRUE
TechnicalContact	info@envirobuild.com



ENVIRO
BUILD

NBS DATA

HYPERION

DECKING



6MM HIDDEN FASTENER

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	A2 grade steel, T15 countersunk screw (6mm head, 3mm shank, 4mm tread) ; 30mm metal or 35mm wood. T15 drill bit
ColourOptions	Black
Recyclability	100%
RecycledContent	100% HDPE
SectionSize	28 x 20 x 11mm (L x W x H)
WaterAbsorption	0%
AcousticRating	n/a
Combustible	TRUE
Material	HDPE
Reference	6mm Hidden Fastener
TechnicalContact	info@envirobuild.com





ENVIRO
BUILD



NBS DATA

HYPERION

DECKING

3MM HIDDEN FASTENER

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	A2 grade steel, T15 countersunk screw (6mm head, 3mm shank, 4mm tread) ; 30mm metal or 35mm wood. T15 drill bit
ColourOptions	Silver
Recyclability	100%
RecycledContent	0%
SectionSize	45 x 30 x 10mm (L x W x H)
WaterAbsorption	0%
AcousticRating	n/a
Combustible	TRUE
Material	304 Grade Stainless Steel
Reference	3mm Hidden Fastener
TechnicalContact	info@envirobuild.com





ENVIRO
BUILD

NBS DATA

HYPERION

DECKING



STARTER FASTENER

IFC	
IfcExportAs IfcCoveringType	IfcExportAs IfcCoveringType
IfcExportType FLOORING	IfcExportType FLOORING
NBS Data	
Accessories	A2 grade steel, T15 countersunk screw (6mm head, 3mm shank, 4mm tread) ; 30mm metal or 35mm wood. T15 drill bit
ColourOptions	Black
Recyclability	100%
RecycledContent	0%
SectionSize	30 x 30 x 10mm (L x W x H)
WaterAbsorption	0%
AcousticRating	n/a
Combustible	TRUE
Material	304 Grade Stainless Steel
Reference	Starter Fastener
TechnicalContact	info@envirobuild.com

