

Shenzhen Toby Technology Co., Ltd.

Report No.: TB-HEA178920

1 of 7 Page:

MPE REPORT

Certificate No. TB210227565

Applicant Shenzhen magwell technology co., limited

Equipment Under Test (EUT)

Brand Name

EUT Name Wi-Fi camera

Model No. TY-S2-U1

TY-SX-XX (X Stand for number) Series Model No.

Receipt Date 2021-02-27

2021-02-27 to 2021-03-10 **Test Date**

2021-03-10 **Issue Date**

Standards EN 62311: 2008

Conclusions PASS

> In the configuration tested, the EUT complied with the standards specified above. The EUT technically complies with the Council Directive 2014/53/EU relating to radio equipment.

> > Ray Lai

Test/Witness Engineer

Engineer Supervisor

in the report.

Engineer Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed

TB-RF-075-1. 0



Report No.: TB-HEA178920 Page: 2 of 7

TABLE OF CONTENTS

1	GEN	IERAL INFORMATION	4
	1.1	Client Information	4
	1.2	General Description of EUT (Equipment Under Test)	4
	1.3	Test Facility	5
2	MAX	(IMUM PERMISSIBLE EXPOSURE	6
	2.1	Standard	6
	2.2	Limit	6
	2.3	Deviation From Test Standard	6
3	TES	T RESULTS SUMMARY	7
	3.1	Transmit Power	7
	3.2	Client Information	7
	3.3	Human Exposure Assessment	7



Report No.: TB-HEA178920 Page: 3 of 7

Revision History

Report No.	Version	Description	Issued Date
TB-HEA178920	Rev.01	Initial issue of report	2021-03-10
TUDE	The same	1000	L One
The state of the s		William William	a Giora
	The same	(103)	TUDE
a Three		1000	THUE
		(103)	Oran A
COURS OF THE PROPERTY OF			a Thirt
The Care		4033	
	N. C.		FULL
		WODA WODA	
The same	100		Charles of the same of the sam
THE PARTY OF THE P			The state of the s



Page: 4 of 7

1 General Information

1.1 Client Information

Applicant		Shenzhen magwell technology co., limited
Address		303, 3rd Floor, Building 12, Dahe Industrial Zone, Guancheng Community, Guanhu Street, Longhua District, Shenzhen, China
Manufacturer	:	Shenzhen magwell technology co., limited
Address	:	303, 3rd Floor, Building 12, Dahe Industrial Zone, Guancheng Community, Guanhu Street, Longhua District, Shenzhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name		Wi-Fi camera		
Model No. :		TY-S2-U1, TY-SX-XX (X Stand for number)		
Model Different :		All these models are identical in the same PCB, layout and electrical circuit, the only difference is the model name.		
Brand Name :		(T) E) (T) E)		
0000		Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2472MHz 802.11n(HT40): 2422MHz~2462MHz	
Product	A	Antenna Gain:	2.5dBi Dipole Antenna	
Description		E.I.R.P:	802.11b: 17.85dbm(Max) 802.11g: 16.07dbm(Max) 802.11n(HT20): 15.94dbm(Max) 802.11n(HT40): 13.54dbm(Max)	
Power Rating	DC 5V from AC/DC adapter:			
Software Version		1.7.5		
Hardware Version	:	J0704_V1 _V1.1 2020107		
Connecting I/O Port(S)	÷	Please refer to the User's Manual		

Note

(2) More information about test, please refer to the RF test report.

⁽¹⁾ For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. This Test Report is EN 62311 for 802.11b/g/n, under RED Article 3.1(a) Healthy.



Page: 5 of 7

1.3 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F.,Building 6, Rundongsheng Industrial Zone, Longzhu, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A.



Page: 6 of 7

2 Maximum Permissible Exposure

2.1 Standard

EN 62311-Assess Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

2.2 Limit

For frequency range 10 MHz to 10 GHz

The basic restriction at frequencies between 10 MHz and 100 GHz is on localized SAR in the head. Any device with output power below 20 mW cannot produce an exposure exceeding this restriction under the most pessimistic exposure conditions. The basic restriction is 2 W/kg so any unit which supplies less than 20 mW (=2/100W) from its antenna port, averaged over 6 minutes, will meet the basic restriction.

For frequency range 10 GHz to 300 GHz

The most conservative assumption is that all the transmitted power is absorbed within the specified area, therefore any device which supplies less than 20 mW will meet the basic restriction. The average time is equal to 68/f-1.05 munutes (where f is in GHz) In the frequency range 10 GHz to 300 GHz, the basic restriction is 10 Wm-2 averaged over any 20 cm² of exposed area with a spatial maximum of 200 Wm-2 averaged over 1 cm²

2.3 Deviation From Test Standard

No deviation



Page: 7 of 7

3 Test Results Summary

3.1 Transmit Power

(1) WiFi

worst Power:

802.11b: 17.85 dBm

More details please refer to RF Test Reports.

3.2 Client Information

RF exposure assessment has been performed below to prove that this unit will not generate the harmful EM emission above the reference level as specified in EC Council Recommendation (1999/519/EC).

3.3 Human Exposure Assessment

EUT parameter	
Max output power in Watt(TP)	17.85dBm (0.06095W)
Antenna Gain (G)	2.5 dBi (Numeric gain:1.7783)
Minimum distance in meter (D) (from transmitting structure to the human body)	0.20m

Exposure Evaluation					
Given	m Cum Process				
	Where G: numerical gain of transmitting				
$E = \frac{\sqrt{30 \times G \times TP}}{2}$	antenna;				
D	TP: Transmitted power in watt;				
./30×1.7783×0.06005	D: Distance from the transmitting				
Yield E= $\frac{\sqrt{30 \times 1.7783 \times 0.06095}}{0.20}$ =9.01V/m	antenna in meter.				

Conclusion:

E=9.01V/m is significant lower than the 61 V/m as required in Annex III table 2 of EC Council Recommendation (1999/519/EC). This proves that the unit complies with the EN62311 for RF exposure requirement.

----END OF REPORT----