



Safety Data Sheet

1. Product And Company Identification

Product Identifier: PLUG-N-SEAL® Drain Stopper (MSD-045)

General Use: PLUG-N-SEAL® Drain Stopper is designed to block and seal a drain to keep a spill and/or contaminants out (see Chemical Guide for compatibility). Several pieces can be overlapped for larger or irregular shapes.

Product Description: A light gray Clay Mat reinforced with polypropylene backing for easier application and puncture resistance, available in various sizes.

COMPANY PROFILE: **EMERGENCY TELEPHONE:**

New Pig Corporation
One Pork Avenue
Tipton, PA 16684-0304
Information Number
1-800-468-4647

INFOTRAC
200 North Palmetto Street
Leesburg, FL 34748
24 hrs, 7 days/week
1-800-535-5053

Website: www.newpig.com, **Email:** hothogs@newpig.com

2. Hazards Identification

GHS Classification: Not a dangerous substance according to GHS

POTENTIAL HEALTH EFFECTS:

Eye Contact: No hazard in normal use of product. Direct contact may cause irritation.

Ingestion: No hazard in normal use of product.

Inhalation: No hazard in normal use of product.

Skin Contact: Not applicable

Chronic: May be harmful if inhaled over a prolonged period.

3. Composition/Information on Ingredients

CAS: 1302-78-9 Bentonite blend Trade Secret
EC: 215-108-5

CAS: 7732-18- Water Trade Secret
EC: 231-791-2

CAS: 57-55-6 Propylene glycol Trade Secret
EC: 200-338-0

CAS: 9003-07-0 Polypropylene backing

4. First Aid Measures

Eye Contact: Flush with water for 15 minutes. Consult a physician if irritation persists.

Ingestion: Not applicable

Inhalation: Not applicable

Skin Contact: Not applicable

5. Fire Fighting Measures

Extinguishing Media: Unused form: Not applicable Used form: that which is compatible to liquid(s) absorbed or diked.

Special Fire Fighting Procedures: If used product is involved in a fire, use extinguishing media appropriate to liquid absorbed or diked.

Hazardous Combustion Products: Not established

Unusual Hazards: Refer to absorbed or diked liquid(s) SDS(s).

The PLUG-N-SEAL® Drain Stopper does not render liquids nonflammable, neutral or less hazardous.

6. Accidental Release Measures

Spill or Leak Procedures: If material is unused, scoop up and dispose of in municipal landfill.

7. Handling and Storage

Handling Precautions: None

Storage Precautions: Store in a cool, dry place. Store above freezing. Shelf Life: ~ 1 year

General: The container can be hazardous when empty. Follow label cautions even after the container is empty. Do not re-use empty containers for food, clothing or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls/Personal Protection

Engineering Controls: Provide general and/or local exhaust ventilation to keep concentrations below PEL/TLV.

PERSONAL PROTECTION

Eyes: Safety glasses with side shields is a good industrial practice

Respirator: Use NIOSH/MSHA approved dust if dust concentrations exceed specified exposure limits.

Gloves: Not normally required. However, when handling bulk, use of cloth, canvas or leather gloves is a good industrial practice.

Other: None required.

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

	EXPOSURE LIMITS 8 hrs. TWA (ppm)	
	OSHA PEL	ACGIH TLV
Mineral nuisance dust:		
Total	15 mg/m ³	10 mg/m ³
Respirable	5 mg/m ³	3 mg/m ³

In its present form, there is little or no dust to present an OSHA hazard



Safety Data Sheet

9. Physical and Chemical Properties

Appearance: Gray clay mat with layer of fabric
Odor: No odor **Odor Threshold:** Not applicable
pH: Not applicable
Melting Point/Freezing Point: 32°F (0°C)
Initial Boiling Point and Range: Not applicable
Flash Point: Not applicable **Method:** Not applicable
Evaporation Rate: Not applicable
Flammable Limits: Not applicable
Conditions of Flammability: Not established
Explosive Properties: Not applicable
Vapor Pressure: Not applicable
Vapor Density: Not applicable
Relative Density (H₂O = 1): 1.4
Solubility in Water: Negligible
Auto-ignition Temperature: Not established
Coefficient of Water/Oil Distribution: Not available

10. Stability and Reactivity

General: This is a stable material.
Conditions of Reactivity: May react with hydrofluoric acid.
Incompatible Materials: Hydrofluoric acid. For compatibility guide, call 1-800-468-4647.
Conditions to Avoid: None
Hazardous Decomposition: None
Hazardous Polymerization: Will not occur

11. Toxicological Information

LD50: Not available
LC50: Not available
Carcinogenicity: IARC: Not established
National Toxicology Program: Not established
OSHA: Not established
California Prop 65: No listed ingredient
Reproduction Toxicity: Not available
Teratogenicity: Not available
Mutagenicity: Not available
Synergistic Products: Not available
Irritancy of Product: See Section 2.
Sensitization to Product: Not available
Bentonite:
Skin: The dermal LD50 for rats is 35 mg/kg
Water:
Ingestion: The oral LD50 for rats is > 90 mL/kg
Propylene glycol:
Ingestion: The oral LD50 for rats is 20 gm/kg

12. Ecological Information

No data available

13. Disposal Considerations

Waste Disposal Method: If unused, no special precautions are necessary. Dispose of in accordance with federal, state and local regulations. In certain types of cleanup applications the nature of the material recovered will classify the resulting spent material as a hazardous component. In such instances the material should be disposed of via an approved hazardous waste disposal service and the appropriate manifesting obtained.

14. Transport Information

DOT (Department of Transportation):
Proper Shipping Name: Not regulated
Hazard Class: Not regulated
Identification Number: Not applicable

15. Regulatory Information

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): No Reportable Quantity
OSHA Hazard Communication Standard, 29 CFR 1910.1200: Mineral nuisance dust
SARA Title III (Superfund Amendments and Reauthorization Act): No listed ingredient
TSCA (Toxic Substances Control Act): Ingredients of this product are on the Inventory list.

16. Other Information

Reason for Issue: Reviewed, changes to Section 16.
Prepared by: Dale Gatehouse, Entreprises Krenda Inc.
Approved by: Lisa Baxter, New Pig Corporation
Approval Date: 02/26/2015
Revised Date: 03/15/2016
SDS Number: MSD-045

The following is in lieu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate.



Safety Data Sheet

1. Product And Company Identification

Product Identifier: PIG Multi-Purpose Repair Putty (MSD-001)

General Use: PIG Multi-Purpose Repair Putty epoxy sticks are used to make emergency patches and repairs of a wide variety of materials.

Product Description: A hand kneadable, fast curing, epoxy adhesive in stick form.

COMPANY PROFILE:	EMERGENCY TELEPHONE:
New Pig Corporation	INFOTRAC
One Pork Avenue	200 North Palmetto Street
Tipton, PA 16684-0304	Leesburg, FL 34748
Information Number	24 hrs, 7 days/week
1-800-468-4647	1-800-535-5053

Website: www.newpig.com, **Email:** hothogs@newpig.com

2. Hazards Identification

Warning! Irritant: Product contains chemicals known to cause skin and eye irritation and may cause sensitization by skin contact.

GHS Classification: Skin corrosion/irritation, Category 2
Serious eye damage/irritation, Category 2
Skin sensitisation, Category 1
Acute aquatic toxicity, Category 3

GHS Label Elements

Signal Word: Warning

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H412 Harmful to aquatic life with long lasting effects

Precautionary Statements:

P264 Wash hands (skin) thoroughly after handling

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 IF ON SKIN: Take off contaminated clothing.

Wash contaminated clothing before reuse.

P332 + P313 IF SKIN irritation occurs: Get medical advice/attention

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention

P501 Dispose of contents and container in accordance with all local, regional, national and international regulations



3. Composition/Information on Ingredients

CAS: 14807-96-6 Talc 30-40%
EC: 238-877-9

CAS: 25068-38-6 Bisphenol-A-epichlorhydrin, epoxy resin
OR

CAS: 25036-25-3 Diglycidyl ether of bisphenol A 10-30%

CAS: 90-72-2 2,4,6-Tri (dimethylaminomethyl) phenol
EC: 202-013-9 1-5%

CAS: 1314-98-3 Zinc Sulfide 1-5%
EC : 215-251-3

CAS: 14808-60-7 Silica, crystalline quartz 0.1-1.0%
EC: 238-878-4

Non-hazardous ingredients meeting the Pennsylvania, Massachusetts and New Jersey Right-To-Know requirements:

Polyether polymercaptan Trade secret
Sodium calcium magnesium silicate 65997-17-3

4. First Aid Measures

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Ingestion: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin Contact: Flush contaminated skin with plenty of soap and water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing and shoes before reuse.

5. Fire Fighting Measures

Extinguishing Media: Use an extinguishing agent suitable for the surrounding fire.

Special Fire Fighting Procedures: Do not breathe fumes. Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, nitrogen oxides, sulfur oxides, halogenated compounds, metal oxide/oxides.

Unusual Hazards: Collect contaminated fire extinguishing water separately. This must not be discharged into drains.



Safety Data Sheet

6. Accidental Release Measures

Spill or Leak Procedures: Wear appropriate personal protective equipment. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place into a designated, labeled waste container. Product should not be released into the environment. Prevent entry into sewers, water courses, basements or confined areas. Dispose of via a licensed waste disposal contractor.

7. Handling and Storage

Handling Precautions: Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Wear impervious gloves when mixing or handling uncured product. Do not ingest. Avoid contact with eyes, skin and clothing. If sanding cured putty or substrates, wear eye protection and dust mask. For prolonged exposure to sanding dust, wear a half face respirator with dust filters. Wash thoroughly after handling, especially before eating, drinking, smoking and using restroom facilities. Wash contaminated goggles, faceshield and gloves. Professionally launder contaminated clothing before re-use.

Storage Precautions: Store in original container protected from direct sunlight in a cool, dry, well ventilated area < 95°F (35°C).
Shelf Life: ~2 years (in original tube with cap on)

General: The container can be hazardous when empty. Follow label cautions even after the container is empty. Do not re-use empty containers for food, clothing or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls/Personal Protection

Engineering Controls: Good general ventilation should be sufficient. Use local exhaust or other engineering controls to keep concentrations below PEL/TLV, or during prolonged sanding operations.

PERSONAL PROTECTION

Eyes: Safety glasses or goggles.

Respirator: None required unless sanding or abrading.

Gloves: Appropriate impervious gloves. Because a variety of protective gloves exist, consult glove manufacturer to determine the proper type for a specific operation.

Other: Ensure that eyewash stations and safety showers are close to the workstation location.

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

EXPOSURE LIMITS 8 hrs. TWA (ppm)

	OSHA PEL	ACGIH TLV
Talc	20 mppcf*	2 mg/m ³ *
Silica, crystalline quartz respirable dust	10 mg/m ³ %SiO ₂ +2	0.025 mg/m ³

* Respirable dust for talc containing no asbestos

9. Physical and Chemical Properties

Appearance: Putty, gray color after cure

Odor: Sulfurous

Odor Threshold: Not applicable

pH: Not applicable

Melting Point/Freezing Point: Not available

Initial Boiling Point and Range: Decomposition temperature: >302°F (>150°C)

Flash Point: >200°F (>93°C) **Method:** Setaflash CC

Evaporation Rate: Not available

Flammability Limits: Not available

Conditions of Flammability: Not available

Explosive Properties: Not available

Vapor Pressure: Not available **Vapor Density:** Not available

Relative Density (H₂O = 1): 1.95

Solubility in Water: Insoluble in cold and hot water

Auto-ignition Temperature: Not available

Coefficient of Water/Oil Distribution: Not available

10. Stability and Reactivity

General: This is a stable material.

Conditions of Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Incompatible Materials and Conditions to Avoid:

Temperatures above 95°F (35°C). Oxidizing agents, acids and bases, amines. For compatibility guide, call 1-800-468-4647.

Hazardous Decomposition: Nitrogen oxides. Combustion produces oxides of carbon including highly poisonous carbon monoxide. Sulphur oxides.

Hazardous Polymerization: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

ACGIH, A2 - Crystalline silica is a suspected human carcinogen

Target Organs: No specific data

POTENTIAL HEALTH EFFECTS:

Eye Contact: Causes serious eye irritation. Symptoms may include pain or irritation, watering, redness.

Ingestion: Irritating to mouth, throat and stomach.

Inhalation: Dusts released from sanding hardened putty may cause irritation to the respiratory tract. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin Contact: Causes skin irritation. Symptoms may include irritation, redness. May cause an allergic skin reaction.

LD50: Not available for mixture

LC50: Not applicable for mixture



Safety Data Sheet

11. Toxicological Information (Cont'd)

Carcinogenicity: Silica, crystalline quartz:
IARC: Category 1
National Toxicology Program: Quartz 14808-60-7
OSHA: See Section 15
California Prop 65: Silica, crystalline (non-respirable). Talc, not containing asbestiform fibers.
Reproduction Toxicity: Not available
Teratogenicity: Not available
Mutagenicity: Not available
Synergistic Products: Not available
Diglycidyl ether of bisphenol A:
Ingestion: The oral LD50 for rats is 11.4 g/kg.
Skin: Severe irritant, Rabbit: 24 hours 2 Milligrams
2,4,6-Tri (dimethylaminomethyl) phenol:
Ingestion: The oral LD50 for rats is 1200 mg/kg.
Skin: The dermal LD50 for rats is 1280 mg/kg.
Skin: Severe irritant, Rat: 0.25 Milliliters

12. Ecological Information

Mobility: Water contaminating.
Persistence and degradability: Not inherently biodegradable
Bioaccumulative potential: Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.
Ozone depletion potential: No ozone depleting chemicals are present or used in manufacture.
Toxicity: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal Considerations

Waste Disposal Method: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contactor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

The following is in lieu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate.

14. Transport Information

DOT (Department of Transportation):
Proper Shipping Name: Putty, NMFC 150110
Hazard Class: Not regulated
Identification Number: Not applicable

15. Regulatory Information

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): No Reportable Quantity
OSHA Hazard Communication Standard, 29 CFR 1910.1200: Crystalline silica, talc (no asbestos fibers).
SARA Title III (Superfund Amendments and Reauthorization Act): Crystalline silica non-respirable, Bisphenol-A-epichlorhydrin epoxy resin, 2,4,6-Tri (dimethylaminomethyl) phenol. This product contains zinc compounds which are subject to the reporting requirements of section 313. They constitute approximately 1-5% of the putty.
TSCA (Toxic Substances Control Act): Ingredients of this product are on the Inventory list.
State regulations:
Massachusetts: Mineral wool fiber; Soapstone
New Jersey: Soapstone; Silica, quartz; Quartz (SiO₂); Zinc compounds
Pennsylvania: Soapstone dust; quartz (SiO₂); Zinc compounds

16. Other Information

WHMIS Classification: D2B

Reason for Issue: Reviewed, changes to Sections 11 & 16.
Prepared by: Dale Gatehouse, Entreprises Krenda Inc.
Approved by: Lisa Baxter, New Pig Corporation
Previous Date of Issue: 02/13/2015
Revised Date: 03/14/2016
SDS Number: MSD-001

Safety Data Sheet

1. Product And Company Identification

Product Identifier: Universal PIG Absorbents (MSD-014)

General Use: Universal PIG Absorbents are designed to confine and absorb leaks, drips, over-spray and spills of a broad range of chemicals, which include oil, water, coolants and solvents.

Specific Product Identifier: PIG Absorbent Mat, PIG Tough Absorbent Mat, PIG Fat Mat Absorbent Mat, PIG Rip-Fit Absorbent Mat, PIG Extra-Duty Absorbent Mat, PIG 4-in-1 Absorbent Mat, PIG 4-All Sock, PIG Chat Mat Absorbent Mat, PIG Yellow Absorbent Mat, PIG Elephant Absorbent Mat, PIG BubbleZorb Anti-Fatigue Absorbent Mat, PIG Barrel Top Absorbent Mat, PIG Yellow Barrel Top Absorbent Mat, PIG Absorbent Diaper Mat, PIG Absorbent Drip Pad, Over-The-Spill Absorbent Pad, PIG Ham-O Absorbent Mat, PIG Rhino Absorbent Mat, PIG Absorbent Drip Pan.

Product Description: These multi-colored absorbents come in a variety of shapes and sizes as mats, pads, rolls, wipes, socks, pillows and pulp. Pan & socks may contain a variety of colored absorbent material.

COMPANY PROFILE:	EMERGENCY TELEPHONE:
New Pig Corporation	INFOTRAC
One Pork Avenue	200 North Palmetto Street
Tipton, PA 16684-0304	Leesburg, FL 34748
Information Number	24 hrs, 7 days/week
1-800-468-4647	1-800-535-5053

Website: www.newpig.com, **Email:** hothogs@newpig.com

2. Hazards Identification

GHS Classification: Not a dangerous substance according to GHS

POTENTIAL HEALTH EFFECTS:

Eye Contact: May cause irritation

Ingestion: No hazard in normal use of product

Inhalation: No hazard in normal use of product

Skin Contact: Not applicable

Chronic: Not applicable

3. Composition/Information on Ingredients

Contains recycled material – Visit www.newpig.com for more information on recycled content.

CAS: 9003-07-0	Polypropylene mat	>97%
CAS: None	Gray or yellow pigment	<0.3%

May contain one or more of the following:

Double Faced Acrylic Adhesive Strip

Pan

CAS: 9002-88-4 High Density Polyethylene

CAS: 9002-86-2 PVC

CAS: 9003-07-0 Polypropylene Mesh or Film

CAS: 25038-59-9 Polyester Yarn, Fleece or Mesh

CAS: 9002-88-4 Polyethylene Film

3. Composition/Information on Ingredients (Cont'd)

Ink

CAS: 1336-21-6 Aqua Ammonia 1-1.5%

EC: 215-647-6

CAS: 108-01-0 Dimethylethanolamine 1-1.5%

EC: 203-542-8

4. First Aid Measures

Eye Contact: Flush with water for 15 minutes. If irritation persists, consult a physician.

Ingestion: Not applicable

Inhalation: Not applicable

Skin Contact: Not applicable

5. Fire Fighting Measures

Extinguishing Media: Unused form: Not applicable Used form: that which is compatible to liquid(s) absorbed.

Special Fire Fighting Procedures: Wear a self-contained breathing apparatus and refer to absorbed liquid(s) SDS(s).

Hazardous Combustion Products: When heated above the melting point: carbon monoxide, carbon dioxide, acrolein, ketones, aldehydes and other unidentified organic compounds.

Unusual Hazards: Refer to absorbed liquid(s) SDS(s). The Universal PIG Absorbents do not render liquids nonflammable, neutral or less hazardous.

6. Accidental Release Measures

Spill or Leak Procedures: If material is unused, sweep or pick up and dispose of as a non-hazardous material.

7. Handling and Storage

Handling Precautions: None

Storage Precautions: Store in a cool, dry place. Shelf Life: Indefinitely - as long as product is kept in a clean, dry place away from direct sunlight.

General: Refer to absorbed liquid(s) SDS(s). The container can be hazardous when empty. Follow label cautions even after the container is empty. Do not re-use empty containers for food, clothing or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls/Personal Protection

Engineering Controls: None required

PERSONAL PROTECTION

Eyes: Safety glasses with side shields is a good industrial practice

Respirator: Not required.

Gloves: Not normally required. However, use of cloth, canvas or leather gloves is a good industrial practice.

Other: None required.



Safety Data Sheet

8. Exposure Controls/Personal Protection (Cont'd)

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):
EXPOSURE LIMITS 8 hrs. TWA (ppm)
OSHA PEL ACGIH TLV

None

9. Physical and Chemical Properties

Appearance: Solid, available in various colors and shapes, some inside a black pan. May contain a variety of colored absorbent material.

Odor: No odor **Odor Threshold:** Not applicable

pH: Not applicable

MELTING POINT/Freezing Point: >320° F (>160° C)

Initial Boiling Point and Range: Not applicable

Flash Point: Not applicable **Method:** Not applicable

Evaporation Rate: Not applicable

Flammable Limits: Not applicable

Conditions of Flammability: Not established

Explosive Properties: Not applicable

Vapor Pressure: Not applicable

Vapor Density: Not applicable

Relative Density (H₂O = 1): 0.9

Solubility in Water: Insoluble

Auto Ignition Temperature: >675° F (>357° C)

Coefficient of Water/Oil Distribution: Not available

10. Stability and Reactivity

General: This is a stable material.

Conditions of Reactivity: Not established

Incompatible Materials: Strong oxidizing agents may degrade product over an extended period of time.

Conditions to Avoid: Not applicable

Hazardous Decomposition: When heated, it may emit toxic fumes.

Hazardous Polymerization: Will not occur

11. Toxicological Information

LD50: Not available

LC50: Not available

Carcinogenicity: IARC: Not established

National Toxicology Program: Not established

OSHA: Not established

California Prop 65: No listed ingredient

Reproduction Toxicity: Not available

Teratogenicity: Not available

Mutagenicity: Not available

11. Toxicological Information (Cont'd)

Synergistic Products: Not available

Irritancy of Product: See Section 2.

Sensitization to Product: Not available

12. Ecological Information

No data available

13. Disposal Considerations

Waste Disposal Method: If unused, no special precautions are necessary. Dispose of in accordance with federal, state and local regulations. In certain types of cleanup applications the nature of the material recovered will classify the resulting spent material as a hazardous component. In such instances the material should be disposed of via an approved hazardous waste disposal service and the appropriate manifesting obtained.

14. Transport Information

DOT (Department of Transportation):

Proper Shipping Name: Not regulated

Hazard Class: Not regulated

Identification Number: Not applicable

15. Regulatory Information

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): No Reportable Quantity

OSHA Hazard Communication Standard, 29 CFR 1910.1200: No listed ingredient

SARA Title III (Superfund Amendments and Reauthorization Act): No listed ingredient

TSCA (Toxic Substances Control Act): Ingredients of this product are on the Inventory list.

16. Other Information

WHMIS Classification: Not a controlled product.

Reason for Issue: Reviewed, changes to Sections 4 & 16.

Prepared by: Dale Gatehouse, Entreprises Krenda Inc.

Approved by: Lisa Baxter, New Pig Corporation

Previous Date of Issue: 02/12/2015

Revised Date: 02/03/2016

SDS Number: MSD-014

The following is in lieu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate.