



Safety Data Sheet

1. Product And Company Identification

Product Identifier: PIG Multi-Purpose Repair Putty (MSD-001)

General Use: PIG Multi-Purpose Repair Putty epoxy sticks are used to make emergency patches and repairs of a wide variety of materials.

Product Description: A hand kneadable, fast curing, epoxy adhesive in stick form.

COMPANY PROFILE:	EMERGENCY TELEPHONE:
New Pig Corporation	INFOTRAC
One Pork Avenue	200 North Palmetto Street
Tipton, PA 16684-0304	Leesburg, FL 34748
Information Number	24 hrs, 7 days/week
1-800-468-4647	1-800-535-5053

Website: www.newpig.com, **Email:** hothogs@newpig.com

2. Hazards Identification

Warning! Irritant: Product contains chemicals known to cause skin and eye irritation and may cause sensitization by skin contact.

GHS Classification: Skin corrosion/irritation, Category 2
Serious eye damage/irritation, Category 2
Skin sensitisation, Category 1
Acute aquatic toxicity, Category 3

GHS Label Elements

Signal Word: Warning

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H412 Harmful to aquatic life with long lasting effects

Precautionary Statements:

P264 Wash hands (skin) thoroughly after handling

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 IF ON SKIN: Take off contaminated clothing.

Wash contaminated clothing before reuse.

P332 + P313 IF SKIN irritation occurs: Get medical advice/attention

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention

P501 Dispose of contents and container in accordance with all local, regional, national and international regulations



3. Composition/Information on Ingredients

CAS: 14807-96-6 Talc 30-40%
EC: 238-877-9

CAS: 25068-38-6 Bisphenol-A-epichlorhydrin, epoxy resin
OR

CAS: 25036-25-3 Diglycidyl ether of bisphenol A 10-30%

CAS: 90-72-2 2,4,6-Tri (dimethylaminomethyl) phenol
EC: 202-013-9 1-5%

CAS: 1314-98-3 Zinc Sulfide 1-5%
EC : 215-251-3

CAS: 14808-60-7 Silica, crystalline quartz 0.1-1.0%
EC: 238-878-4

Non-hazardous ingredients meeting the Pennsylvania, Massachusetts and New Jersey Right-To-Know requirements:

Polyether polymercaptan Trade secret
Sodium calcium magnesium silicate 65997-17-3

4. First Aid Measures

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Ingestion: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin Contact: Flush contaminated skin with plenty of soap and water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing and shoes before reuse.

5. Fire Fighting Measures

Extinguishing Media: Use an extinguishing agent suitable for the surrounding fire.

Special Fire Fighting Procedures: Do not breathe fumes. Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, nitrogen oxides, sulfur oxides, halogenated compounds, metal oxide/oxides.

Unusual Hazards: Collect contaminated fire extinguishing water separately. This must not be discharged into drains.



Safety Data Sheet

6. Accidental Release Measures

Spill or Leak Procedures: Wear appropriate personal protective equipment. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place into a designated, labeled waste container. Product should not be released into the environment. Prevent entry into sewers, water courses, basements or confined areas. Dispose of via a licensed waste disposal contractor.

7. Handling and Storage

Handling Precautions: Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Wear impervious gloves when mixing or handling uncured product. Do not ingest. Avoid contact with eyes, skin and clothing. If sanding cured putty or substrates, wear eye protection and dust mask. For prolonged exposure to sanding dust, wear a half face respirator with dust filters. Wash thoroughly after handling, especially before eating, drinking, smoking and using restroom facilities. Wash contaminated goggles, faceshield and gloves. Professionally launder contaminated clothing before re-use.

Storage Precautions: Store in original container protected from direct sunlight in a cool, dry, well ventilated area < 95°F (35°C).
Shelf Life: ~2 years (in original tube with cap on)

General: The container can be hazardous when empty. Follow label cautions even after the container is empty. Do not re-use empty containers for food, clothing or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls/Personal Protection

Engineering Controls: Good general ventilation should be sufficient. Use local exhaust or other engineering controls to keep concentrations below PEL/TLV, or during prolonged sanding operations.

PERSONAL PROTECTION

Eyes: Safety glasses or goggles.

Respirator: None required unless sanding or abrading.

Gloves: Appropriate impervious gloves. Because a variety of protective gloves exist, consult glove manufacturer to determine the proper type for a specific operation.

Other: Ensure that eyewash stations and safety showers are close to the workstation location.

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

EXPOSURE LIMITS 8 hrs. TWA (ppm)

	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Talc	20 mppcf*	2 mg/m ³ *
Silica, crystalline quartz respirable dust	$\frac{10 \text{ mg/m}^3}{\% \text{SiO}_2+2}$	0.025 mg/m ³

* Respirable dust for talc containing no asbestos

9. Physical and Chemical Properties

Appearance: Putty, gray color after cure

Odor: Sulfurous

Odor Threshold: Not applicable

pH: Not applicable

Melting Point/Freezing Point: Not available

Initial Boiling Point and Range: Decomposition temperature: >302°F (>150°C)

Flash Point: >200°F (>93°C) **Method:** Setaflash CC

Evaporation Rate: Not available

Flammability Limits: Not available

Conditions of Flammability: Not available

Explosive Properties: Not available

Vapor Pressure: Not available **Vapor Density:** Not available

Relative Density (H₂O = 1): 1.95

Solubility in Water: Insoluble in cold and hot water

Auto-ignition Temperature: Not available

Coefficient of Water/Oil Distribution: Not available

10. Stability and Reactivity

General: This is a stable material.

Conditions of Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Incompatible Materials and Conditions to Avoid:

Temperatures above 95°F (35°C). Oxidizing agents, acids and bases, amines. For compatibility guide, call 1-800-468-4647.

Hazardous Decomposition: Nitrogen oxides. Combustion produces oxides of carbon including highly poisonous carbon monoxide. Sulphur oxides.

Hazardous Polymerization: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

ACGIH, A2 - Crystalline silica is a suspected human carcinogen

Target Organs: No specific data

POTENTIAL HEALTH EFFECTS:

Eye Contact: Causes serious eye irritation. Symptoms may include pain or irritation, watering, redness.

Ingestion: Irritating to mouth, throat and stomach.

Inhalation: Dusts released from sanding hardened putty may cause irritation to the respiratory tract. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin Contact: Causes skin irritation. Symptoms may include irritation, redness. May cause an allergic skin reaction.

LD50: Not available for mixture

LC50: Not applicable for mixture



Safety Data Sheet

11. Toxicological Information (Cont'd)

Carcinogenicity: Silica, crystalline quartz:
IARC: Category 1
National Toxicology Program: Quartz 14808-60-7
OSHA: See Section 15
California Prop 65: Silica, crystalline (non-respirable). Talc, not containing asbestiform fibers.
Reproduction Toxicity: Not available
Teratogenicity: Not available
Mutagenicity: Not available
Synergistic Products: Not available
Diglycidyl ether of bisphenol A:
Ingestion: The oral LD50 for rats is 11.4 g/kg.
Skin: Severe irritant, Rabbit: 24 hours 2 Milligrams
2,4,6-Tri (dimethylaminomethyl) phenol:
Ingestion: The oral LD50 for rats is 1200 mg/kg.
Skin: The dermal LD50 for rats is 1280 mg/kg.
Skin: Severe irritant, Rat: 0.25 Milliliters

12. Ecological Information

Mobility: Water contaminating.
Persistence and degradability: Not inherently biodegradable
Bioaccumulative potential: Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.
Ozone depletion potential: No ozone depleting chemicals are present or used in manufacture.
Toxicity: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal Considerations

Waste Disposal Method: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contactor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

The following is in lieu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate.

14. Transport Information

DOT (Department of Transportation):
Proper Shipping Name: Putty, NMFC 150110
Hazard Class: Not regulated
Identification Number: Not applicable

15. Regulatory Information

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): No Reportable Quantity
OSHA Hazard Communication Standard, 29 CFR 1910.1200: Crystalline silica, talc (no asbestos fibers).
SARA Title III (Superfund Amendments and Reauthorization Act): Crystalline silica non-respirable, Bisphenol-A-epichlorhydrin epoxy resin, 2,4,6-Tri (dimethylaminomethyl) phenol. This product contains zinc compounds which are subject to the reporting requirements of section 313. They constitute approximately 1-5% of the putty.
TSCA (Toxic Substances Control Act): Ingredients of this product are on the Inventory list.
State regulations:
Massachusetts: Mineral wool fiber; Soapstone
New Jersey: Soapstone; Silica, quartz; Quartz (SiO₂); Zinc compounds
Pennsylvania: Soapstone dust; quartz (SiO₂); Zinc compounds

16. Other Information

WHMIS Classification: D2B

Reason for Issue: Reviewed, changes to Sections 11 & 16.
Prepared by: Dale Gatehouse, Entreprises Krenda Inc.
Approved by: Lisa Baxter, New Pig Corporation
Previous Date of Issue: 02/13/2015
Revised Date: 03/14/2016
SDS Number: MSD-001