

October 1, 2010

Mr. Mark Woytowich Business Platform Leader Foodservice Division New Pig Corporation One Pork Ave Tipton, PA 16684

Dear Mr. Woytowich

The PIG® Grippy Absorbent Walk-on Surface was tested per the ANSI/NFSI B101.1-2009 Test Method for Measuring Wet SCOF of Common Hard-Surface Floor Materials on September 16, 2010 and the average Static Coefficient of Friction (SCOF) was 0.98 which exceeds our minimum acceptable wet SCOF value of a 0.6. Walkways that posses a wet SCOF of 0.6 or greater are defined by the standard as "High-Traction". When used as part of a floor safety program, these high-traction surfaces have been proven to reduce slip and fall claims by as much as 90%.

Please feel free to contact us if you have any questions. Thank you.

Sincerely,

Russell J Kendzior

President



September 20, 2010

Mr. Mark Woytowich Business Platform Leader Foodservice Division New Pig Corporation One Pork Ave Tipton, PA 16684

Dear Mr. Woytowich:

On behalf of the National Floor Safety Institute I would like to thank you for submitting your product for Phase 1 testing. The PIG<sup>®</sup> Grippy™ Absorbent Walk-on Surface was tested per the ANSI/NFSI B101.1-2009 Test Method for Measuring Wet SCOF of Common Hard-Surface Floor Materials on September 16, 2010 and the average Static Coefficient of Friction (SCOF) was 0.98 which exceeds our minimum acceptable wet SCOF value of a 0.6 and is therefore eligible for Phase 2 testing.

The purpose of the ANSI/NFSI B101.1-2009 is to determine the wet Static Coefficient Of Friction (SCOF) of hard surfaced flooring materials using the BOT-3000. The product was tested per Phase 1 of our certification process and does not reflect real-world performance as evaluated in Phase 2 testing.

Please feel free to contact us if you have any questions. Thank you.

Sincerely,

Russell J. Kendzior

President