

# PIG® Poly Modular Spill Deck

#PAK529 - Holds 2 Drums • Use With Plastic & Steel Drums • 22 gal. Sump Capacity



Connectable, shared-sump decks let you build up to your required sump capacity to help meet containment regs.

- Patented "flow-through" sump design lets liquid pass freely from one sump to another to help you comply with containment regulations
- Modular design features exclusive bulkhead fittings and predrilled ports to connect to other decks; ready to use as soon as they arrive
- Mix and match the sections you need to fit your space and help meet sump capacity requirements
- Special tools and hardware to connect sections is included with each system
- Low-profile 5.75"H design is easy to load or unload; pumps and funnels are easy to access
- Molded-in sump catches leaks, drips and spills to help keep your storage areas clean and safe
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating adds traction and lifts out for easy sump access
- Translucent white sidewalls allow easy visual inspection
- We test all of our PIG Containment Deck designs at max load for months to ensure they can handle full capacity at your facility



By Phone:  
**+1-814-684-0101**

Online:  
**[newpig.com/International](http://newpig.com/International)**

Email:  
**[hothogs@newpig.com](mailto:hothogs@newpig.com)**

**New Pig International**

One Pork Avenue • Tipton PA 16684-0304  
© 2016 New Pig Corporation. All rights reserved.  
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PAK529 - Pg 1 of 3

# PAK529 Specifications

|                                   |   |
|-----------------------------------|---|
| <b>Color:</b>                     | White/Black   |
| <b>Dimensions:</b>                | 26" W x 52" L x 5.75" H                             |
| <b>Recycled Content:</b>          | 43% Post-Industrial Recycled Polyethylene           |
| <b>Load Capacity UDL:</b>         | 3000 lbs.   |
| <b>Sump Capacity:</b>             | 22 gal.   |
| <b>Containment Type:</b>          | Containment Deck                                    |
| <b>Double-Stackable Unit:</b>     | No  |
| <b>Drain:</b>                     | No Drain  |
| <b>Fork Truck Access:</b>         | No Fork Truck Access                                |
| <b>Grates:</b>                    | (1) 48" L x 24" W Grate                             |
| <b>Groundable for Flammables:</b> | No  |
| <b>Number of Containers:</b>      | 2 Drums   |
| <b>Type of Container:</b>         | Plastic & Steel Drums                               |
| <b>Sold as:</b>                   | 1 each  |
| <b>Weight:</b>                    | 45 lbs.   |
| <b>New Pig Patent:</b>            | Patent 5,562,047; And Other Foreign Patents         |
| <b># per Pallet:</b>              | 20  |
| <b>Composition:</b>               | Sump - LDPE w/ UV Inhibitor<br>Grate - Polyethylene |
| <b>Includes:</b>                  | 1 - Hardware Kit (PAK477)                           |
| <b>UNSPSC:</b>                    | 24101905  |

# PAK529 Metric Equivalent

|                           |                               |
|---------------------------|-------------------------------|
| <b>Dimensions:</b>        | 66cm W x 132.1cm L x 14.6cm H |
| <b>Load Capacity UDL:</b> | 1360.8 kg                     |
| <b>Sump Capacity:</b>     | 83.3 L                        |
| <b>Weight:</b>            | 20.4 kg                       |

# PAK529 Accessories

| You might like...   |                         | Item Number |
|---|-------------------------|-------------|
|  | PIG® Steel Loading Ramp | PAK538      |
|  | PIG® Poly Loading Ramp  | PAK726      |

# Technical Information

## Warnings & Restrictions:

**Flammables Notice**  
If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.

## Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps, be designed to keep spilled liquids from remaining in contact with the container, prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers, or the volume of the largest container, whichever is greater."

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

## Technical Documents:

(Available at [newpig.com/International](http://newpig.com/International))

Product Data Sheet (PDS)

Chemical Compatibility (CCG)



By Phone:  
**+1-814-684-0101**

Online:  
**[newpig.com/International](http://newpig.com/International)**

Email:  
**[hothogs@newpig.com](mailto:hothogs@newpig.com)**



PIG® Poly Modular Spill Deck

PAK524



PIG® Poly Modular Spill Deck

PAK531



By Phone:  
**+1-814-684-0101**

Online:  
**[newpig.com/International](http://newpig.com/International)**

Email:  
**[hothogs@newpig.com](mailto:hothogs@newpig.com)**

**New Pig International**

One Pork Avenue • Tipton PA 16684-0304  
© 2016 New Pig Corporation. All rights reserved.  
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PAK529 - Pg 3 of 3