



Super Swamp Boom

BOM100 For Calm Water & Low Current, 25' x 10", 6" Draft Dimensions

Non-absorbent floating booms quickly contain oil spills and small debris in swamps or calm, shallow waters.

- Round, closed-cell polyethylene flotation cylinders contain oil and debris up to 4" above water line
- Skirting barrier hangs 6" below water line to keep pollutants from creeping under
- Galvanized steel chain runs length of boom to add weight and rigidity
- Heavy-duty, 22-ounce vinyl-coated polyester with welded seams resists UV in regular outdoor use
- Link units using marine-grade aluminum universal slide connectors and attached toggle pins
- 1,800 lb. actual breaking strength
- Polypropylene handle/anchor point allows easy one-person deployment from barges, boats, trailers, docks or shore
- High-visibility yellow speeds recognition in emergencies
- Conforms to OPA-90 specifications
- Cleans easily using detergent, steam or power washing
- Easy to transport and store
- Add PIG Oil-Only Booms to absorb petroleumbased pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)

Specifications

Style	Non-Absorbent Boom
Color	Yellow
Dimensions	25' L x 10" H
Current Type	Calm Water & Low Current
Intended Use	On Water
Sold as	1 each
Weight	24 lbs.
Composition	Boom - PVC Chain - Galvanized Steel
Application	Spill Response

Draft Dimensions	6"
Freeboard Dimensions	4"
UNSPSC	24101907
Pigalog® Page Number	Page 193
Metric Equivalent	
Dimensions	8m L x 25.4cm H
Weight	10.9 kg
Technical Information	
Certifications, Approvals and Ratings	
AASHTO M-228 Erosion Class A	
Technical Documents	

33 CFR 154.1040

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com