



EconoMax Boom

BOM104 For Calm Water & Low Current, 50' x 16", 10" Draft Dimensions

Economical non-absorbent floating booms provide 1,800 lb. of actual breaking strength to contain waterborne oil spills and debris on calm water.

- Rectangular, closed-cell polyethylene foam flotation blocks corral liquids and debris up to 6" above the water line
- Skirting barrier hangs 10" below the water line to keep pollutants from creeping under
- Galvanized steel chain runs the length of the boom to add weight and rigidity
- Heavy-duty, 22-ounce vinyl-coated polyester is UV resistant for regular outdoor use
- Welded, reinforced seams ensure long life
- Marine-grade aluminum universal slide connectors and attached toggle pins let you link multiple booms
- Quality construction provides 1,800 lb. actual breaking strength
- Compact size allows easy deployment
- High-visibility yellow for instant recognition in emergencies
- Conforms to OPA-90 specifications; ideal for economical use in inner harbors, marinas and waterways
- Cleans easily using detergents, steam or power washing
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)

Specifications

| | |
|---------------------|--|
| Style | Non-Absorbent Boom |
| Color | Yellow |
| Dimensions | 50' L x 16" H |
| Current Type | Calm Water & Low Current |
| Intended Use | On Water |
| Sold as | 1 each |
| Weight | 70 lbs. |
| Composition | Boom - PVC Chain - Galvanized Steel |
| Application | Spill Response |

| | |
|-----------------------------|-----------------|
| Draft Dimensions | 10" |
| Freeboard Dimensions | 6" |
| UNSPSC | 24101907 |
| Pigalog® Page Number | <u>Page 193</u> |

Metric Equivalent

| | |
|-------------------|------------------|
| Dimensions | 15m L x 40.6cm H |
| Weight | 31.8 kg |

Technical Information

Certifications, Approvals and Ratings

AASHTO M-228 Erosion Class A

Technical Documents

33 CFR 154.1040

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com