

Tundra Guard Boom

BOM108 For Calm Water & Low Current, 50' x 14", 8" Draft Dimensions

Ideal for tides and other waters that vary in height, these non-absorbent floating booms can seal to the ground in shallow areas to contain oil spills and debris.

- Round, closed-cell microfoam flotation cylinders corral liquids and debris up to 6" above water line
- Fill water ballast chamber to create weighted barrier that floats 8" below water line or seals to the ground in shallow spots to block pollutants
- Heavy-duty, 22-ounce vinyl-coated polyester with welded seams resists UV in regular outdoor use
- Link units without escape points for liquid or debris using marine-grade aluminum universal slide connectors and attached toggle pins
- 5,000 lb. actual breaking strength
- Polypropylene handle/anchor point allows easy one-person deployment from barges, boats, trailers, docks or shore
- High-visibility yellow speeds recognition in emergencies
- Conforms to OPA-90 specifications
- Cleans easily using detergent, steam or power washing
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)



Specifications

| | |
|-------------------------|--|
| Style | Non-Absorbent Boom |
| Color | Orange/Yellow |
| Dimensions | 50' L x 14" H |
| Current Type | Calm Water & Low Current |
| Intended Use | On Water |
| Sold as | 1 each |
| Weight | 105 lbs. |
| Composition | Boom - PVC Chain - Galvanized Steel |
| Application | Spill Response |
| Draft Dimensions | 8" |

| | |
|----------------------|-----------------|
| Freeboard Dimensions | 6" |
| UNSPSC | 24101907 |
| Pigalog® Page Number | <u>Page 193</u> |

Metric Equivalent

| | |
|------------|------------------|
| Dimensions | 15m L x 35.6cm H |
| Weight | 47.6 kg |

Technical Information

Certifications, Approvals and Ratings

AASHTO M-228 Erosion Class A

Technical Documents

33 CFR 154.1040

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com