



## Optimax I Boom

BOM118 For Moderate Current, 100' x 19", 12" Draft Dimensions

Contain oil spills and debris in rough waters with the 6,400 lb. breaking strength of durable non-absorbent floating Optimax I Booms.

- Round polystyrene flotation boom corrals liquids and debris while skirting hangs below to keep pollutants from creeping under
- Vinyl-coated, UV-resistant polyester withstands up to 12-month deployment; 6,400 lb. breaking strength
- Link multiple booms with aluminum universal slide connectors
- Nylon handles allow single-person handling and anchoring
- Conforms to OPA-90 specs for protected water and fast currents
- Ideal in streams, rivers, estuaries, near-shore ocean environments and other areas with moderately fast flow
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)

### Specifications

<b>Style</b>	Non-Absorbent Boom
<b>Color</b>	Yellow
<b>Dimensions</b>	100' L x 19" H
<b>Current Type</b>	Moderate Current
<b>Intended Use</b>	On Water
<b>Sold as</b>	1 each
<b>Weight</b>	200 lbs.
<b>Composition</b>	Skin - PVC Flotation - Polystyrene Chain - Galvanized Steel
<b>Application</b>	Spill Response
<b>Draft Dimensions</b>	12"
<b>Freeboard Dimensions</b>	7"
<b>UNSPSC</b>	24101907
<b>Pigalog® Page Number</b>	Page 193

### Metric Equivalent

**Dimensions**

30m L x 48.3cm H

**Weight**

90.7 kg

**Technical Information****Certifications, Approvals and Ratings**

AASHTO M-228 Erosion Class A

**Technical Documents**

33 CFR 154.1040

33 CFR 154.545(a)

40 CFR 112.7

40 CFR 122.26

**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)