





BOM406 3" x 10', Absorbs up to 2 gal. per boom, 8 booms

Confine and absorb oil and fuel spills on water.

- Absorbs and retains oils and oil-based liquids including lubricants and fuels - without taking in a drop of water
- Booms float at surface for easy retrieval, even when saturated
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets NFPA 99 standards for static decay
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending





NSN (National Stock Number)



Specifications

Fluid Absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Color	White
Dimensions	ext. dia. 3" x 10' L
Recycled Content	98% Pre-Consumer Recycled Polypropylene Filler
Absorbency	Up to 16 gal. per bag
Absorbency per	Up to 2 gal. per boom
Clip/Ring	Zinc Plated Carbon Steel
Filler	Polypropylene
Skin/Outer Mesh	Skin - Polypropylene, Outer Mesh - Polyester
Sold as	8 booms per bag
Weight	24 lbs.

7930-01-436-8327

# per Pallet	18
Application	Spill Response
UNSPSC	47131907
Pigalog® Page Number	Page 65
Metric Equivalent	

Absorbency per Up to 7.6 L per boom

Up to 60.6 L per bag

Dimensions ext. dia. 7.6cm x 3m L

Weight 10.9 kg

Technical Information

Certifications, Approvals and Ratings

NFPA 99

Technical Documents

UV-Resistance Comparison Testing of Spunbond and Meltblown

Instructions for Using PIG® Absorbent Booms

Spill Response Training: Absorbent Booms

PIG® Oil-Only Absorbents

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com