









BOM409 8" x 20', Absorbs up to 24 gal. per boom, 2 booms

Confine and absorb oil and fuel spills on water.

- Absorbs and retains oils and oil-based liquids including lubricants and fuels - without taking in a drop of water
- Booms float at surface for easy retrieval, even when saturated
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets NFPA 99 standards for static decay
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending







Specifications

per Pallet

Fluid Absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Color	White
Dimensions	ext. dia. 8" x 20' L
Recycled Content	98% Pre-Consumer Recycled Polypropylene Filler
Absorbency	Up to 48 gal. per bag
Absorbency per	Up to 24 gal. per boom
Clip/Ring	Zinc Plated Carbon Steel
Filler	Polypropylene
Skin/Outer Mesh	Skin - Polypropylene, Outer Mesh - Polyester
Sold as	2 booms per bag
Weight	55 lbs.
Sold as	2 booms per bag

8

Application	Spill Response
UNSPSC	47131907
Pigalog® Page Number	Page 65

Metric Equivalent

Absorbency per	Up to 90.8 L per boom
Absorbency	Up to 181.7 L per bag
Dimensions	ext. dia. 20.3cm x 6m L

24.9 kg

Technical Information

Certifications, Approvals and Ratings

NFPA 99

Weight

Technical Documents

Instructions for Using PIG® Absorbent Booms

Spill Response Training: Absorbent Booms

PIG® Oil-Only Absorbents

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com