



PIG® Grippy® Adhesive-Backed Absorbent Mat

MAT3200 Mediumweight, (10) 16" x 24" pads, 10 pads

Make the switch to the mat that sticks to prevent slips, trips and falls around workstations and walkways near machinery in industrial facilities.

- Adhesive-backed absorbent mat stays exactly where you put it with no shifting, bunching up or flipping over to prevent slips, trips and falls in workstations and around machinery
- Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily for quick changeouts; reduces cleanup time to make your facility more productive
- Sticks to most commercial floor surfaces including concrete, VCT, linoleum, ceramic tile, quarry tile and laminate flooring
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to foot and lightwheeled traffic; keep mat in service until it's saturated or shows signs of wear
- Eight layers of fine-fiber polypropylene safely absorb leaks, drips and overspray of oils, coolants, solvents and water
- Traps oil, grease and grime to keep them from being tracked around; ideal for oily areas near machines and equipment
- 16" x 24" mat pads are great for catching drips and lining workbenches, countertops and toolboxes
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark color hides grime so the mat looks cleaner longer
- Easy to cut and install: just roll it out, stick it down and smooth it out
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Absorbent Mat have been proven to reduce slip-and-fall claims by as much as 90%
- Mats take on the properties of absorbed liquids
 always take proper precautions when handling saturated absorbents



Specifications

| Antimicrobial | No | |
|-----------------------------|--|--|
| Traffic | Medium Foot Traffic | |
| Backing Material | Adhesive-Backed | |
| Indoor/Outdoor | Indoor Use | |
| Pad Quantity | (10) 16" x 24" pads | |
| Incinerable | Yes | |
| Flammability Specifications | Flame Resistant - Will melt and self-extinguish | |
| Fluid Absorbed | Oils, Coolants, Solvents, Water – Universal | |
| Color | Blue | |
| Dimensions | 16" W x 24" L | |
| Mat Weight | Mediumweight | |
| Recycled Content | 25% or more Recycled Content | |
| Absorbency | Up to 1 gal. per box | |
| Absorbency per | Up to 12.8 oz. per pad | |
| Brand | PIG | |
| Category | Grippy® Absorbent Mat | |
| Industry | Industrial Facilities; Shops & Garages | |
| Perforated | No | |
| Storage Temp Range | Store between 32°F and 120°F | |
| Temperature Limit | Surface temps from 55°F to 120°F | |
| Walking Surface | Absorbent Top | |
| Sold as | 10 pads per box | |
| Weight | 3.86 lbs. | |
| New Pig Patent | Patent Pending | |
| # per Pallet | 128 | |
| Composition | Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material | |
| UNSPSC | 47131901 | |
| UV Resistant | No | |
| Pigalog® Page Number | Page 19 | |
| Metric Equivalent | | |
| Absorbency per | Up to 378.5 mL per pad | |
| Absorbency | Up to 3.8 L per box | |

| D 1 | | |
|------------|------|-------|
| Dim | ens | ions |
| | CIIC | 10113 |

Weight

1.8 kg

Certifications, Approvals and Ratings

NFSI Certified, ANSI B101.1- 2009, Meets NFPA 99 Static Decay and Resistivity Requirements

Technical Documents

Technical Information

PIG Grippy® Absorbent Mat

Static Coefficient Of Friction (SCOF) Testing

- How to use PIG Grippy Absorbent Mat
- White paper Slip & Fall Prevention Secrets
- New Pig Adhesive-Backed Mat Notice
- PIG Adhesive-Backed Mats ADA Compliance
- PIG® Grippy® Absorbent Mats

29 CFR 1910.22(a)(2)

Disclaimers

Safety Instructions Regarding Flammable Liquids for Flame Resistant Mats

Pig Absorbent Mats are flame resistant in their unused state, but take on the properties of flammable liquids they absorb. Always take proper precautions against potential ignition in handling and disposal of these mats if they have absorbed flammable liquids. For further assistance, please call Technical Services.

Color Variation Statement

It is normal for top layer materials to show minor variations in color between production runs. This is particularly true for the grades of materials used in consumable or disposable products such as our adhesive-backed mats. New Pig makes every effort to achieve consistent color, but some variance is possible. Perceived differences in color may also result from mat layout orientation or uneven traffic wear patterns.



One Pork Avenue • Tipton, PA 16684-0304 1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com