


PIG® SpillBlocker® Rough Surface Dike



PLR230 Ideal For One-Time-Use Emergency Spill Response, One 2" W x 10' L x 2.25" H Section

Our Rough-Surface Dike stops spills on asphalt in their tracks with a liquid-tight tacky bottom layer that seeps into surface cracks.

- Exclusive New Pig formulation features a tear-resistant top layer with a super-tacky bottom layer that seals tight to rough surfaces and blocks liquids
- Bottom layer "seeps" into surface cracks to form a liquid-tight seal
- Fast protection for when a spill is heading right for your drain on a rough surface; just set dike down with sticky side away from surface, turn dike over and press into place
- Intended for one-time, limited term use; ideal for containing hazardous or other liquids on rough surfaces
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- 2.25" height contains spills up to 2" deep
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow top color draws attention to spill for increased safety
- Light-weight dike is easy to handle and deploy



Specifications

Traffic	Non-Weight Bearing
Barrier Dimensions	One 2" W x 10' L x 2.25" H Section
Color	Yellow
Dimensions	2" W x 10' L x 2.25" H
Ideal For	One-Time-Use Emergency Spill Response
Install/Deploy Type	Temporary/Removable Barrier
Intended Use	Rough Surfaces and Asphalt
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes
Storage Temp Range	Store Between 0°F and 120°F
Temperature Limit	Works from 0°F to 160°F
Sold as	1 per box

Weight	13 lbs.
New Pig Patent	5,236,281
# per Pallet	32
Composition	Polyurethane
Includes	1 - PIG® SpillBlocker® Rough Surface Dike 1 - Connector 1 - Polyethylene Disposal Bags (BAG201-S)
UNSPSC	24101907
Pigalog® Page Number	<u>Page 165</u>

Metric Equivalent

Dimensions	5.1cm W x 3m L x 5.7cm H
Weight	5.9 kg

Technical Information

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[Instructions for PIG SpillBlocker Rough Surface Dike](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com