

Dike Corner

PLR268 For SpillBlocker Dike, 1 each

Turn the corner with your SpillBlocker Dikes using this leakproof 90-degree connector.

- Add this handy corner piece to a pair of SpillBlocker Dikes to create a 90° angle
- Built-in dovetail connectors form a liquid-proof seal
- Build any shape or configuration to suit your application or environment



ltem#	Description	Dimensions	Weight
PLR268-BK	Black,	4.75" W x 5" L x 3" H	2 lbs.
Metric Equivalent:			
Item#	Description	Dimensions	Weight
PLR268-BK	Black,	12.1cm W x 12.7cm L x 7.6cm H	.9 kg
Specifications			
Use With		SpillBlocker Dike	
Dimensions		4.75" W x 5" L x 3" H	
Max liquid temp exposure		Max Exposure Limit 225°F for	r up to 30 Minutes
Temperature Limit		Works from 0°F to 160°F	
Sold as		1 each	
Weight		2 lbs.	
New Pig Patent		5,236,281	
# per Pallet		882	
Composition		Polyurethane	
UNSPSC		24101907	
Pigalog® Page Number		Page 163	

Metric Equivalent

Dimensions	12.1cm W x 12.7cm L x 7.6cm H		
Weight	.9 kg		
Technical Information			
Technical Documents			
PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers			
Urethane Use, Care and Storage			
White paper – Should I be Worried about SPCC? 8 Things you need to know.			
PIG® Blocker Family			
40 CFR 112.7			
40 CFR 122.26			
Disclaimers			

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com