

## **PIG® DrainBlocker® Drain Cover**

PLR408 Ideal For Repeated Use or Frequent Washdowns, For Rectangular Drains Up to 54" x 30"

Protect your storm drains with the patented design that seals tight and won't rip. Guaranteed.

- Patented two-layer design seals tight to protect drains and won't rip. Guaranteed.
- Use cover for quick spill response or long-term, outdoor deployment without worrying about degradation
- Vinyl composite top layer resists stretching, ripping and tearing
- DuPont Elvaloy technology provides lifelong flexibility plus chemical, UV and infrared light resistance to vinyl top
- Super-sealing urethane bottom layer conforms to uneven surfaces and tightly seals drain openings to block liquid
- Cover withstands prolonged exposure to diesel fuel and gasoline, even when completely submerged
- Ideal for drain protection where liquid transfers, washdowns or other leak- and spill-prone jobs are common
- Eliminates the need to frequently deploy and remove a temporary cover or permanently seal your drains
- High-visibility yellow top layer draws attention to spills for increased safety
- Need a custom size? Call 1-800-HOT-HOGS (468-4647)
- Note: Elvaloy top can become slippery when wet. Please use caution.



### Specifications

Traffic	Foot Traffic
Use With	Rectangular Drains Up to 54" x 30"
Color	Yellow
Dimensions	36" W x 60" L x 0.335" H
Drain Shape	Rectangular
Drain Size	Up to 54" x 30"

<b>Ideal For</b>	Repeated Use or Frequent Washdowns
<b>Max liquid temp exposure</b>	Max Exposure Limit 225°F for up to 30 Minutes
<b>Storage Temp Range</b>	Store from 0°F to 120°F
<b>Temperature Limit</b>	Works from 0° to 160°F
<b>Sold as</b>	1 each
<b>Weight</b>	32 lbs.
<b>New Pig Patent</b>	8,117,686
<b># per Pallet</b>	32
<b>Composition</b>	Top - DuPont™ Elvaloy® Vinyl Bottom - Urethane
<b>UNSPSC</b>	40141739
<b>UV Resistant</b>	Yes
<b>Pigalog® Page Number</b>	<u><a href="#">Page 173</a></u>

## Metric Equivalent

<b>Dimensions</b>	91.4cm W x 152.4cm L x 8.5mm H
<b>Weight</b>	14.5 kg

## Technical Information

### Technical Documents

[PIG DrainBlocker Drain Cover with DuPont Elvaloy](#)

[Submersion Test of PIG® DRAINBLOCKER® Drain Cover with DuPont™ Elvaloy® Technology](#)

[Urethane Use, Care and Storage](#)

[White paper – Should I be Worried about SPCC? 8 Things you need to know.](#)

[Instructions for PIG® Drainblocker® Drain Cover](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

### Disclaimers

#### Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)

