

PIG® DrainBlocker® Drain Cover

PLR412 Ideal For Repeated Use or Frequent Washdowns, For Round Drains Up to 6" Dia.

Protect your storm drains with the patented design that seals tight and won't rip. Guaranteed.

- Patented two-layer design seals tight to protect drains and won't rip. Guaranteed.
- Use cover for quick spill response or long-term, outdoor deployment without worrying about degradation
- Vinyl composite top layer resists stretching, ripping and tearing
- DuPont Elvaloy technology provides lifelong flexibility plus chemical, UV and infrared light resistance to vinyl top
- Super-sealing urethane bottom layer conforms to uneven surfaces and tightly seals drain openings to block liquid
- Cover withstands prolonged exposure to diesel fuel and gasoline, even when completely submerged
- Ideal for drain protection where liquid transfers, washdowns or other leak- and spill-prone jobs are common
- Eliminates the need to frequently deploy and remove a temporary cover or permanently seal your drains
- High-visibility yellow top layer draws attention to spills for increased safety
- Note: Elvaloy top can become slippery when wet. Please use caution.



Specifications

Traffic	Foot Traffic
Use With	Round Drains Up to 6" Dia.
Color	Yellow
Dimensions	ext. dia. 12" x 0.335" H
Drain Shape	Round
Drain Size	Up to 6" Dia.
Ideal For	Repeated Use or Frequent Washdowns
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes

Storage Temp Range	Store from 0°F to 120°F
Temperature Limit	Works from 0° to 160°F
Sold as	1 each
Weight	3 lbs.
New Pig Patent	8,117,686
# per Pallet	100
Composition	Top - DuPont™ Elvaloy® Vinyl Bottom - Urethane
UNSPSC	40141739
UV Resistant	Yes
Pigalog® Page Number	<u>Page 173</u>

Metric Equivalent

Dimensions	ext. dia. 30.5cm x 8.5mm H
Weight	1.4 kg

Technical Information

Technical Documents

[PIG DrainBlocker Drain Cover with DuPont Elvaloy](#)

[Submersion Test of PIG® DRAINBLOCKER® Drain Cover with DuPont™ Elvaloy® Technology](#)

[Urethane Use, Care and Storage](#)

[White paper – Should I be Worried about SPCC? 8 Things you need to know.](#)

[Instructions for PIG® Drainblocker® Drain Cover](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com

