









PLR516 For 1.5" High Drive-Over Build-A-Berm Barrier, 2 each

Drive-over barrier springs back into shape when heavy vehicles, carts, dollies and pallet jacks pass. Custom containment berm helps you control liquids in high-traffic areas.

- The PIG Drive-Over Build-A-Berm Barrier provides semi-permanent containment in hightraffic areas on concrete, asphalt or most sealed surfaces
- Constructed of 40-ounce, vinyl-coated fabric with an open-cell foam core; berm compresses to approximately 1/4" when driven over; springs back to shape when vehicles pass
- 1.5" height accommodates low-clearance traffic like pallet jacks, heavy carts and dollies; durable enough to withstand indoor or outdoor traffic from trucks, loaded tow motors and other heavy vehicles
- Secure to floor with sealant and reinforce with predrilled aluminum mounting strips and steel anchors; seal seams with vinyl cement
- Create any configuration by combining with other Build-A-Berm components; ends overlap and can be sealed together for liquid-proof containment
- When used with standard Build-A-Berm Barriers, orange color indicates area where drivers can enter and exit
- Sealed, 90-degree wall end sits flush against the floor and a wall, curb, etc.
- Helps you create professional containment areas without fabrication or using excessive caulk



Specifications

Use With	1.5" High Drive-Over Build-A-Berm Barrier
Color	Orange
Dimensions	4.5" W x 6" L x 1.5" H
Temperature Limit	Works from -22°F to 160°F
Sold as	2 per box

Weight 2 lbs.

New Pig Patent	5,820,297
# per Pallet	100
Composition	Cover - 40 oz. PVC Core - Open-Cell Polyurethane Foam Strips - Aluminum Anchors - Galvanized Steel
UNSPSC	24101907
Pigalog® Page Number	Page 171

Metric Equivalent

Dimensions	11.4cm W x 15.2cm L x 3.8cm H
Weight	.9 kg

Technical Information

Technical Documents

PIG Build-A-Berm® Barrier

Instructions for PIG Drive-Over Build-A-Berm Barrier

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com