PIG® Epoxy Putty for Wet Surfaces

#PTY259 - Repair Putty • Wet Surface • 6 each





Special PIG Epoxy Putty formulations cover nearly any application. Guaranteed to work or your money back.

- Specially formulated with the highest-quality epoxy resins to bond to wet surfaces, even cures underwater!
- Convenient, premeasured epoxy has Parts A and B in one tube so you can fix it fast
- Mixes easily simply by kneading to a uniform color
- After curing, can be drilled, sawed, sanded, filed, tapped, machined or painted
- 20-minute working time
- Resists yellowing from UV
- Ideal for reparing fittings, pipes, electrical connections, leaky gaskets, sinks, tanks and boats

PTY259 Specifications

Style: Repair Putty

Color: Gray
Dimensions: 7" L

Application: Wet Surface Handling Time: 20 Minutes

Pipe Pressure: Pressurized, Non-Pressurized

Pipe Size: Unlimited
Repair Type: Permanent

Temperature Limit: 250°F (121°C) Continuous, 300°F (149°C)

Intermittent

Sold as: 6 per box Weight: 3 lbs.

Composition: 15% Epoxy Resins

1.5% Catalyst

83.5% Non-Hazardous Proprietary Ingredient

UNSPSC: 31201607

Technical Information

Warnings & Restrictions:

This product is subject to export restrictions and cannot be shipped to Canada.

Certifications, Approvals and Ratings:

Meets USDA requirements

Technical Documents:

(Available at newpig.com/International)

Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)

PTY259 Metric Equivalent

Dimensions: 17.8cm L **Weight:** 1.4 kg

