

PIG® Epoxy Putty for Steel

#PTY264 - Repair Putty • Steel • 6 each



Special PIG Epoxy Putty formulations cover nearly any application. Guaranteed to work or your money back.

- Specially formulated with the highest-quality epoxy resins to bond and blend with ferrous metals
- Convenient, premeasured epoxy has Parts A and B in the same tube
- Mixes easily simply by kneading to a uniform color
- After curing, can be drilled, sawed, sanded, filed, tapped, machined or painted
- 3- to 5-minute working time
- Can be used indoors or out
- A great addition to any toolbox or response kit



New Pig International

By Phone:
+1-814-684-0101

Online:
newpig.com/International

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304

© 2016 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PTY264 - Pg 1 of 2

PTY264 Specifications

Style:	Repair Putty
Color:	Gray
Dimensions:	7" L
Application:	Steel
Handling Time:	3 Minutes
Pipe Pressure:	Pressurized, Non-Pressurized
Pipe Size:	Unlimited
Repair Type:	Permanent
Temperature Limit:	250°F (121°C) Continuous, 300°F (149°C) Intermittent
Sold as:	6 per box
Weight:	2 lbs.
Composition:	15% Epoxy Resins 1.5% Catalyst 83.5% Non-Hazardous Proprietary Ingredient
UNSPSC:	31201607

Technical Information

Warnings & Restrictions:

This product is subject to export restrictions and cannot be shipped to Canada.

Technical Documents:

(Available at newpig.com/International)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)

PTY264 Metric Equivalent

Dimensions:	17.8cm L
Weight:	.9 kg



New Pig International

By Phone:
+1-814-684-0101

Online:
newpig.com/International

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304
© 2016 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PTY264 - Pg 2 of 2