

## SPECIFICATIONS

|                             |  |
|-----------------------------|--|
| <b>Item : GT- SWL-18-6K</b> |  |
| Light Brightness            | 1000 Lumens  |
| <b>Solar panel</b>          |  |
| Power                       | Monocrystalline , 1.5W   |
| <b>Li-ion battery</b>       |  |
| Capacity                    | 3.7V/2000mAH (7.4WH)   |
| Charging/Discharging Temp   | 0~45°C / -20~60°C  |
| Charging Time               | 6.5H   |
| LED                         | 2835 20pcs   |
| Color Temp                  | 6000K , Ra 80+   |
| Efficiency                  | 190lm/W  |
| UV LED                      | -  |
| <b>Performance</b>          |  |
| Lighting Time in Rainyday   | >10 days   |
| Control Mode                | Button Switch , ON/OFF Long Press 1.5s                                   |
| Lighting Mode               | M1: 100LM + PIR 1000LM(10S)<br>M2: 0LM+PIR 1000LM (10S)<br>M3: 300LM(6H) |
| Mode Indication             | Red LED : M1: One Blink M2: Two Blink M3: Three Blink                    |
| Capacity Indication         | -  |
| PIR                         | Yes  |
| Core technology             | ALS 2.3/ TCS 1.0   |
| Solar Panel Autoclean       | -  |
| IP/IK Class                 | IP65   |
| Install Height              | 2.5M-3.5M  |