

Item: GT06ST-M

Light Brightness	3000 lumens
------------------	-------------

Solar panel

Power	Monocrystalline, 20W
-------	----------------------

Li-ion battery

Capacity	14.8V, 115.44 WH 2.6AH/PC
----------	---------------------------

Charging/Discharging Temp	0~45°C / -20~60°C
---------------------------	-------------------

Charging Time	6.6H
---------------	------

LED (OSRAM)	3030 40pcs
-------------	------------

Color Temp	4000k/6000k, Ra 70+
------------	---------------------

Efficiency	190lm/W
------------	---------

UV LED	-
--------	---

Performance

Lighting Time in Rainyday	>10 days
---------------------------	----------

Control Mode	Button Switch, ON/OFF Long Press 1.5s
--------------	---------------------------------------

Lighting Mode	M1: 20%+PIR (100%) / M2: 65%(5H)+15% (PIR) (5H) +45% / M3: 45% constant brightness
---------------	--

Mode Indication	M1: RED / M2: GREEN / M3: ORANGE
-----------------	----------------------------------

Capacity Indication	Green Light: ≥70% Orange Light: 30%~70% Red Light: <30%
---------------------	---

PIR	120° 8m
-----	---------

Core technology	ALS2.2
-----------------	--------

Self-Cleaning Function	-
------------------------	---

IP/IK Class	IP65 / IK08
-------------	-------------

Installation Height	5M
---------------------	----