## **Arlington**® SNAP<sup>2</sup>IT<sup>®</sup> Connectors



**38AST** 





40AST



Zinc die-cast. For AC • MCI-A • HCF steel and aluminum cable • Flexible metal conduit steel and aluminum (regular and reduced wall) • MCI cable • Continuous corrugated aluminum • AC90 SNAP-TITE® and SNAP2IT® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page 7.

## **NO TOOLS!**

- Safe and fast installations
- Saves about 17 seconds per fitting!
- Competitively priced

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE						DIM C		CABLE RANGE
38AST*	00070	3/8	1/2	50	500	1.410	.850	.405	1.000	.405612
38A*	00038	3/8	1/2	50	500	1.410	.850	.405	1.000	.405612
380ST	00381	3/8	1/2	50	500	1.284	.850	.400	1.000	.405612
380AST*	00382	3/8	1/2	50	500	1.410	.850	.400	1.000	.405612

\*Provided with insulated throat.

Flexible metal conduit, CSA Listed with anti-short bushing ONLY. PATENTED.

## WITH INSULATED THROAT AND RED TINTED INSIDE CLIP

	UPC/DCI/NAED MFG #018997									CABLE RANGE
40AST	00041	3/8	1/2	50	500	1.410	.850	.405	1.000	.485612
400AST	40347	3/8	1/2	50	500	1.410	.850	.400	1.000	.485612
40A	48015	3/8	1/2	50	500	1.280	.850	.400	1.000	.485612

Flexible metal conduit, CSA Listed with anti-short bushing ONLY.

Refer to chart on page E-27 for list of cable types. See page E-30 and E-31 for MCI-A cable ranges. Concrete tight when taped. PATENTED.











INSTALLATION INSTRUCTIONS

COMPARE...

SNAP<sup>2</sup>IT Connectors are EASY to Install...



Snap fitting onto cable and twist clockwise.

**38AST** 



Snap assembly into the box.

40AST

And EASY to Remove...



Using a screwdriver, lift the ring and twist off.

## **RED TINTING means** 'OPEN TANG' Design!

It gives you **more room** inside the fitting for easy insertion of wires. The redesigned front end makes it easier than ever to snap the fitting into box!

**E-1** 

www.aifittings.com | Tel: (800)233-4717 | Fax: (570)562-0646 | Email: Sales@aifittings.com



