

Shield Damper Piston

Instruction Manual


caution

This products fits only M's Products damper and TAMIYA TRF damper.


Feature of Shield Damper Piston

- 1)Piston is made of PTFE so you can get smooth action of piston
- 2)O-ring around the piston makes the damper like real damper.
- 3)Piston thickness is thicker than conventional type that makes damping force more effective

装着方法




Damper piston



Mount o-ring to piston



Mount E-ring to upper side first



Put piston from lower part of shaft

Mount o-ring to the periphery of the piston

- 1)mount the O-ring to the periphery of the piston. Make sure that o-ring is compressed to the gap. (photo2)
Mount the E-ring to upper side of the shaft
- 2)piston thickness is 3mm. You can not set the piston if you mount the E-ring lower side first.(photo3)
Put the piston from lower part of the shaft(photo4)
Mount the E-ring to lower side of the shaft
- 3)If you feel rattling of piston , use spacer to prevent rattling.(spacer is including in package. 0.15mm)

We have three kind of holes 0.6mm 0,8mm 1.0mm diameter

- 1)0.6mm、6holes : total size of holes 1.69m²
- 2)0.8mm、3holes : total size of holes 1.50m²
- 3)1.0mm、3holes : total size of holes 2.35m²

Manufacturer



製造元:株式会社 エムズプロダクト
〒271-0081千葉県松戸市二十世紀が丘美野里町17
☎047-393-8108



販売元:株式会社 SPEC販売
〒141-0032東京都品川区大崎3-6-21-209
☎03-3782-2310