



website: www.bartact.com
phone: 951-319-4008
email: orders@bartact.com

INSTALLATION INSTRUCTIONS: 2007-2016 JK 4 dr Bench Covers

1. Starting with the front Driver's seat you will install the rear seat covers. There will be two separate sizes for the rear seat covers, identify the smaller side of the bench seat (behind the Driver's seat) which covers the 1 seat and the larger side of the bench seat (behind the Passenger's seat) which covers both seats.

You will start with installing the bottom (seat) of the smaller bench seat.

Open the seat cover and loosely fit it around the seat. Next, slide the seat back down about 1/3 of the way. This will allow you easier access to slide the seat cover on. Now, use the same process and feed the Velcro section thru the joining sections of the seat and seat back and thru to the other side. Adhere the Velcro to for a snug fit



2. Next will be the seat back on the same seat.

Remove the headrest from the seat by depressing the two (2) clips on the top of the seat. You cannot see this clips, however they will be just under the headrest on the bottom where the post feeds into the headrest. This will allow you to pull the headrest up and off the headrest posts.

Now you will slide the seat back cover down. Make sure the headrest posts feed thru the openings at the top of the seat cover and that the opening for the seat handle is lined up.

Now, use the same process and feed the Velcro section thru the joining sections of the seat and seat back and thru to the other side. Adhere the Velcro to for a snug fit



3. Next you will install the seat cover on the larger section of the bench seat.

You will start with installing the bottom (seat) of the larger bench seat.

Open the seat cover and loosely fit it around the seat. Next, slide the seat back down about 1/3 of the way. This will allow you easier access to slide the seat cover on. Now, use the same process and feed the Velcro section thru the joining sections of the seat and seat back and thru to the other side. Adhere the Velcro to for a snug fit



4. Next will be the seat back on the same seat.

First, you will need to remove the seat belt from the middle of the rear seat. Using an 18MM socket, remove the bolt. Pull the seat belt out thru the front of the seat.

Remove the headrest from the seat by depressing the two (2) clips on the top of the seat. These will be the same as the other rear seat headrest.

Take the seat belt that you had removed and feed it up and thru the top of the seat back cover. Now you will be able to slide the seat back cover down. Make sure the headrest posts feed thru the openings at the top of the seat cover and that the opening for the seat handle is lined up.

Now, use the same process and feed the Velcro section thru the joining sections of the seat and seat back and thru to the other side. Adhere the Velcro to for a snug fit

Lastly, bolt the seatbelt back into place and torque it down to factory specifications.



5. Once all seat covers are on, do a once over on all of the seats, to ensure a snug fit and reseat the Velcro as needed.