BOAT BOMB

Page: 1

Compilation date: 21/07/2022

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BOAT BOMB

Product code: 1677

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: AUGUST RACE WORLDWIDE LTD

UNIT 7 THE SAIL LOFT

SINGERS YARD, PAIGNTON

DEVON

TQ32AH United

Kingdom

Tel: 01803 224363

Fax:

Email: info@august-race.com

1.4. Emergency telephone number

Emergency tel: 01803 224363

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10

Classification under CLP: Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame



BOAT BOMB

Page: 2

Signal words:	Danger
Precautionary statements:	P210: Keep away from heat, hot surfaces, sparks, open flames and other
	ignition sources. No smoking.
	P211: Do not spray on an open flame or other ignition source.
	P251: Do not pierce or burn, even after use.
	P261: Avoid breathing spray.
	P410+412: Protect from sunlight. Do not expose to temperatures
	exceeding 50 °C.
	P501: Dispose of contents/container to hazardous or special waste
	collection point.
Label elements under CHIP:	
Hazard symbols:	Flammable.
	*
Risk phrases:	R10: Flammable.
Safety phrases:	S23: Do not breathe spray.
	S38: In case of insufficient ventilation, wear suitable respiratory equipment.
Precautionary phrases:	Pressurised container: protect from sunlight and do not expose to
	temperatures exceeding 50°C. Do not pierce or burn, even after use.
	Do not spray on a naked flame or any incandescent material. Keep away
	from sources of ignition - No smoking. Keep out of the reach of children.
2.3. Other hazards	

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL - REACH registered number(s): 01-2119457610-43

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-578-6	64-17-5	F: R11 Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	30- 50%

BUTANE

203-448-7	106-97-8	F+: R12 Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10- 30%
		workplace exposure limit.		

BOAT BOMB

Page: 3

PROPANE				
200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10- 30%
ISOBUTANE				
200-857-2	75-28-5	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10- 30%
3-IODO-2-PRO	OPYNYL BUTYL	CARBAMATE		
259-627-5	55406-53 -6	Xn: R22; T: R23; Xi: R41; Sens.: R43; T: R48/23; N: R50	Acute Tox. 3: H331; Acute Tox. 4: H302; STOT RE 1: H372; Eye Dam. 1: H318; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%
Section 4:	First aid me	easures		
41 5	accription of	first aid measures		
4.2	Ingestio Inhalatio	a litre of water to drink immRemove casualty from expo	water for 15 minutes. Consult a doctors sh out mouth with water. If conscious rediately. Consult a doctor. sure ensuring one's own safety whilst ualty sits or lies down. Move to fresh apours. Consult a doctor.	, give half doing so.
4.2. M	iost importar	it symptoms and effects, bot	n acute and delayed	
	Eye contae	n: There may be difficulty swal	at the site of contact. redness. The eyes may water profuse lowing. Headaches or general malaise ng and diarrhoea. The casualty may a	e may
		Exposure may cause coughi confusion may occur. There	ne throat with a feeling of tightness in ng or wheezing. Drowsiness or menta may be loss of consciousness.	
			spected after short-term exposure.	4
4.3.1		any immediate medical atten	tion and special treatment needed	
Section 5:	Fire-fightin	g measures		

5.1. Extinguishing media

Extinguishing media: Use water spray to cool containers. Suitable extinguishing media for the surrounding fire should be used.

BOAT BOMB

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Fire exposed aerosols should be sprayed with water to reduce risk of rupture/explosion. Contents of aerosol will add to fuelling of fire.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Eliminate all sources of ignition. If outside keep bystanders upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

BOAT BOMB

Page: 5

Hazardous ingredients:

ETHANOL

могкріасе е	exposure limits:	R	espirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	
BUTANE				
UK	1450 mg/m3	1810 mg/m3	-	
PROPANE				
UK	1800 mg/m3	7200 mg/m3	_	
SOBUTANE				
UK	2400 mg/m3	9600 mg/m3	_	

DNEL / PNEC No data available.

DNEL / PNEC	No data available.
8.2. Exposure contro	ls
Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and
Respiratory protection:	electrical equipment are not a source of ignition. Self-contained breathing apparatus must be available in case of
	emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses.
Skin protection:	Protective clothing.
Environmental:	No special requirement.
Section 9: Physical and (chemical properties

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol		
Colour:	Colourless		
Odour:	Pleasant		
Evaporation rate:	Fast		
Oxidising:	Not applicable.		
Solubility in water:	Slightly soluble		
Also soluble in:	Most organic solvents.		
Viscosity:	Non-viscous		
Boiling point/range°C:	<100	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	-20	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	Not applicable.	pH:	Not applicable.
VOC g/l:	No data available.		[cont]

BOAT BOMB

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

DERMAL	RBT	LD50	>2000	mg/kg
ORL	MUS	1H LC50	>20	mg/kg
ORL	RAT	LD50	>2000	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

- **Ingestion:** There may be difficulty swallowing. Headaches or general malaise may result. There may be vomiting and diarrhoea. The casualty may appear intoxicated. There may be loss of consciousness.
- **Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Drowsiness or mental confusion may occur. There may be loss of consciousness.

BOAT BOMB

Page: 7

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ETHANOL

ALGAE	48H EC50	>100	mg/l
Daphnia magna	48H EC50	>100	mg/l
FISH	96H LC50	>100	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

BOAT BOMB

Page: 8

		rage. 0
14.4. Packing group		
14.5. Environmental	hazards	
Environmentally hazardous:	No Ma	rine pollutant: No
14.6. Special precaut		•
	Limited Quantity - 1 Litre	
Tunnel code:		
Transport category:		
Section 15: Regulatory i		
mixture	and environmental regulations/legislatio	n specific for the substance of
15.2. Chemical Safet	v Assessment	
Section 16: Other inform	nation	
Other information		
Other information:	This safety data sheet is prepared in accorda	ance with Commission
	Regulation (EU) No 453/2010.	
	* indicates text in the SDS which has change	ed since the last revision.
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.	
	H222: Extremely flammable aerosol.	
	H225: Highly flammable liquid and vapour.	
	H229: Pressurised container: May burst if he	ated
	H302: Harmful if swallowed.	
	H317: May cause an allergic skin reaction.	
	H318: Causes serious eye damage.	
	H331: Toxic if inhaled.	
	H372: Causes damage to organs <or a<="" state="" td=""><td>II organs affected, if known></td></or>	II organs affected, if known>
	through prolonged or repeated exposure <st< td=""><td>ate route of exposure if it is</td></st<>	ate route of exposure if it is
	conclusively proven that no other routes of e	exposure cause the hazard>.
	H410: Very toxic to aquatic life with long las	ting effects.
	H412: Harmful to aquatic life with long lastir	ng effects.
	R10: Flammable.	
	R11: Highly flammable.	
	R12: Extremely flammable.	
	R22: Harmful if swallowed.	
	R23: Toxic by inhalation.	
	R41: Risk of serious damage to eyes.	
	R43: May cause sensitisation by skin contact	
	R48/23: Toxic: danger of serious damage to	health by prolonged exposure
	through inhalation.	
	P50: Very toxic to aquatic organisms	[cont]

R50: Very toxic to aquatic organisms.

BOAT BOMB

Page: 9

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.