

# Single Speed Fans (On/Off)

**WhisperGreen**  
VENTILATION FAN



**FV-05VK3** 50 CFM 4" or 6" Duct  
**FV-08VK3** 80 CFM 4" or 6" Duct  
**FV-11VK3** 110 CFM 4" or 6" Duct

### WhisperGreen Key Benefits:

- SmartFlow™ technology for optimal CFM output
- Fully enclosed DC motor for long life – rated for 60,000 hours continuous run
- Detachable dual 4" or 6" duct adaptor included
- Fits in 2 x 8 construction

WhisperGreen	FV-05VK3		FV-08VK3		FV-11VK3	
Characteristics						
Static pressure in inches w. g.	0.1	0.25	0.1	0.25	0.1	0.25
Air Volume (CFM)	50	54	80	79	110	112
Noise (sones)	<0.3	0.3	<0.3	0.4	0.3	0.8
Power Consumption (Watts)	4.3	7.5	7.0	11.0	11.5	16.2
Energy Efficiency (CFMs/Watt)	12.4	7.7	12.1	7.6	9.7	7.0
Speed	749	1101	832	1130	953	1229
Current	0.05	0.02	0.02	0.01	0.21	0.30
Power Rating (V/Hz)	120/60					



CALGreen



**WhisperCeiling**  
VENTILATION FAN



**FV-05VQ5** 50 CFM 4" or 6" Duct  
**FV-08VQ5** 80 CFM 4" or 6" Duct  
**FV-11VQ5** 110 CFM 4" or 6" Duct

**FV-15VQ5** 150 CFM 6" Duct

### WhisperCeiling Key Benefits:

- Detachable dual 4" or 6" duct adaptor on 50-110 CFM models
- Fits in 2 x 8 construction

WhisperCeiling	FV-05VQ5		FV-08VQ5		FV-11VQ5		FV-15VQ5	
Characteristics								
Static pressure in inches w. g.	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Volume (CFM)	50	36	80	62	110	91	150	127
Noise (sones)	<0.3	0.5	<0.3	0.4	<0.3	0.5	<0.3	0.5
Power Consumption (Watts)	11.0	11.5	14.7	14.5	21.1	20.7	28.4	27.3
Energy Efficiency (CFMs/Watt)	4.7	3.2	5.8	4.5	5.3	4.5	5.3	4.7
Speed	731	1060	829	1089	950	1161	691	911
Current	0.09	0.10	0.12	0.12	0.18	0.17	0.24	0.23
Power Rating (V/Hz)	120/60							



CALGreen



**WhisperFit**  
VENTILATION FAN



INCLUDED:  
4 to 3 inch adaptor

**FV-05VF2** 50 CFM 4" or 3" Duct  
**FV-08VF2** 80 CFM 4" or 3" Duct  
**FV-11VF2** 110 CFM 4" or 3" Duct

### WhisperFit Key Benefits:

- Low profile housing design – Ideal for remodeling!
- Fits in 2 x 6 & 2 x 8 construction

WhisperFit	FV-05VF2		FV-08VF2		FV-11VF2							
Characteristics	4" Duct	3" Duct	4" Duct	3" Duct	4" Duct	3" Duct						
Static pressure in inches w. g.	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25				
Air Volume (CFM)	50	30	50	31	80	60	70	53	110	94	90	78
Noise (sones)	0.4	0.9	0.5	1.1	0.8	1.0	0.8	1.1	1.5	1.5	1.5	2.0
Power Consumption (Watts)	15.0	14.7	15.0	14.8	24.5	24.3	24.3	24.0	33.5	33.2	33.8	33.5
Energy Efficiency (CFMs/Watt)	3.3	2.0	3.3	2.1	3.3	2.5	2.9	2.2	3.3	2.8	2.7	2.3
Speed	637	932	741	978	757	956	845	1007	830	1000	1029	1128
Current	0.13	0.12	0.13	0.12	0.20	0.20	0.20	0.20	0.28	0.28	0.28	0.28
Power Rating (V/Hz)	120/60		120/60		120/60		120/60					



CALGreen



**WhisperValue**  
VENTILATION FAN



### WhisperValue U-Can Contractor Pack

The Contractor Pack includes four complete fans. The housing and motor/grille are packaged separately for flexibility during installation.

Universal Housing Can	Motor/Grille Assembly	Complete Fan Unit	Master Pack
FV-05-08VSA1	FV-05VSB1	FV-05VS1	4
FV-05-08VSA1	FV-08VSB1	FV-08VS1	4
FV-05-08VSA1	FV-10VSB1	FV-10VS1	4

**FV-05VS1** 50 CFM 4" Oval Duct  
**FV-08VS1** 80 CFM 4" Oval Duct  
**FV-10VS1** 100 CFM 4" Oval Duct

### WhisperValue Key Benefits:

- Super low profile housing design
- UL listed for wall or ceiling installation
- Fits in 2 x 4, 2 x 6 & 2 x 8 construction

WhisperValue	FV-05VS1		FV-08VS1		FV-10VS1	
Characteristics	4" Oval Duct		4" Oval Duct		4" Oval Duct	
Static pressure in inches w. g.	0.1	0.25	0.1	0.25	0.1	0.25
Air Volume (CFM)	50	37	80	71	100	90
Noise (sones)	0.4	1.0	1.3	1.5	1.5	1.5
Power Consumption (Watts)	18.1	17.8	27.4	27.6	36.4	36.1
Energy Efficiency (CFMs/Watt)	3.2	2.4	3.4	2.8	2.9	2.7
Speed (RPM)	759	948	878	1026	840	979
Current (amps)	0.04	0.04	0.11	0.11	0.30	0.30
Power Rating (V/Hz)	120/60		120/60		120/60	