

Model Number: Accessories: Job:	Approvals: Type:
---------------------------------------	-------------------------

RDG-R RECESSED ADJUSTABLE GIMBAL RING

- Constructed of rugged steel in neutral cream finish
- Mounting plate allows fast, easy installation in suspended T-grid or drywall ceilings
- Suitable for damp locations
- Adjustable, glare-free lighting head

Part No.	Volts	Watts	Lamp Type
RDG-R	6V	7.2	Halogen

Mounting Plate & Trim: included
Lamp Head: RDG-R



L1D THERMOPLASTIC WEDGE BASED SQUARE

- Constructed of impact resistant, UL 94 V-0 thermoplastic
- White or black with matching mounting plate included
- Add "2" prefix for double head mounting plates

Part No.	Volts	Watts	Lamp Type
L1D	6V	5.4	Tungsten
L2D	6V	7.2	Tungsten
L3D	6V	9	Tungsten
L4D	12V	7.2	Tungsten
L5D	12V	12	Tungsten



Mounting Plate: included
Lamp Head: L1D



Mounting Plate: included
Lamp Head: 2L1D

L1H THERMOPLASTIC BI-PIN HALOGEN SQUARE

- Constructed of impact resistant, UL 94 V-0 thermoplastic
- White or black with matching mounting plate included
- 6 volt, 5 watt bi-pin halogen lamps
- Add "2" prefix for double head mounting plate

Part No.	Volts	Watts	Lamp Type
L1H	6V	5	Halogen



Mounting Plate: included
Lamp Head: L1H



Mounting Plate: included
Lamp Head: 2L1H

Z1P-B THERMOPLASTIC WET LOCATION RATED

- NEMA 4X rated sealed beam PAR 36
- Constructed of gray polycarbonate
- Lamp heads are fully gasketed
- Add "2" prefix for double head mounting plates

Part No.	Volts	Watts	Lamp Type	Color
Z1P-B	6V	7.2	Tungsten	Gray
Z5P-B	12V	12	Tungsten	Gray
Z14P-B	6V	9	Tungsten	Black
Z15P-B	12V	12	Tungsten	Black



Mounting Plate: included
Lamp Head: Z1P-B



Mounting Plate: included
Lamp Head: 2Z1P