

Intelligent-WeighTM Rugged NTEP Toploading Scale



- NTEP / Measurement Canada Approved
- Bench Portion Weigher
- Rechargeable Battery
- Large Backlit Display
- High Capacity
- Optional RS-232 Interface













A Higher Level of Precision . . . A Higher Level of Performance



Model	XM-1500	XM-3000	XM-6000	XM-15	XM-30
Capacity	3 lb 1,500 g 48 oz	6 lb 3,000 g 96 oz	12 lb 6,000 g 192 oz	30 lb 15 kg 480 oz	60 lb 30 kg 960 oz
Readability	0.001 lb 0.5 g 0.02 oz	0.002 lb 1 g 0.05 oz	0.005 lb 2 g 0.1 oz	0.01 lb 5 g 0.2 oz	0.02 lb 10 g 0.5 oz
Divisions	3,000				
Weighing Units	lb / g / oz lb / kg / oz				
Stabilization Time	< 1.5 seconds				
Tare Range	To capacity by subtraction				
Power Source	Built-in rechargeable battery or external power adapter (included)				
Construction	ABS pan with stainless steel insert and ABS housing				
Display	1 inch / 25.4 mm wide viewing angle LCD with backlight				
Pan Size (W x D)	9.84 x 8.46 inches / 250 x 215 mm				
Overall Dimensions (W x D x H)	9.4 x 11.2 x 4.1 inches / 240 x 285 x 105 mm				
Operating Environment	32 °F to 104 °F non condensing R.H. ≤ 85%				
Connectivity	RS 232 configurable interface				
Net Weight	5.9 lb / 12.67 kg				
Shipping Weight	11 lb / 5 kg				
Options	RS-232 Interface, Additional Stainless Steel Platter Cover, Printer				
Approvals	NTEP CoC #11-106 Measurement Canada Approval #AM-5839				

Features	Benefits		
Heavy duty construction with overload and underload stops	Will withstand harsh industrial operation		
Low profile, compact size	Uses less counter space		
Built-in rechargeable battery or external power	Portability – battery lasts a minimum of 150 hours		
Auto zero tracking	Ensures that you always start weighing at zero		
Automatic power save	Conserves battery power		
Low battery indicator	Alerts you to charge the battery, saving downtime		
Easy calibration function	Ensures accuracy		
Adjustable feet	Scale remains level for accurate results even on uneven working surfaces – anti-slip		
Wide-angle backlit LCD display	Can be seen from a wide viewing range		
In use cover	Keeps scale clear from contamination		
Easy calibration function	Ensures accuracy		
Reads in grams, pounds, and lb:oz	Flexibility in operation		
Zero tracking	Ensures that you always start weighing at zero		
Automatic power save / standby indicator	Conserves battery power		
Built-in rechargeable battery or external power adapter	Portability – battery lasts minimum of 150 hours		
In-use cover	Keeps scale clear of contamination		