



Corrugated Stainless Steel Flexible Water Heater/Softener Connectors Specification Sheet

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater &/or Softener Connectors

DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- True .72" ID
- Flows approx 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer
- Chlorine and Chloramine Resistant
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG
- * ICC Listed, Tested & Certified
- * UPC, IPC, IMC, IRC (USA)
- * Low Lead Compliant California H & S Code 116875
- * ASME A112.18.6/CSA B125.6-2009 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

<u>Model #</u>	<u>Description</u>	<u>Length</u>
H3402		
FF-12	3/4" FIP x 3/4" FIP	12"
FF-15	3/4" FIP x 3/4" FIP	15"
FF-18	3/4" FIP x 3/4" FIP	18"
FF-24	3/4" FIP x 3/4" FIP	24"
FF-36	3/4" FIP x 3/4" FIP	36"
FF-48	3/4" FIP x 3/4" FIP	48"



<u>Product Submittal</u>	
Job Name:	_____
Date:	_____
Model#	Quantity: _____

Architect/Contractor: _____	

