



### Corrugated Stainless Steel Flexible Water Heater/ Softener Connectors Specification Sheet

#### SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater/Softener Connector

#### DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer
- Chlorine and Chloramine Resistant
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

#### COMPLIANCES/LISTINGS:

- \* ICC-ES PMG
- \* ICC Listed, Tested & Certified
- \* UPC, IPC, IMC, IRC (USA)
- \* Low Lead Compliant California H & S Code 116875
- \* ASME A112.18.6/CSA B125.6-2009 Compliant
- \* NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

Model #	Description	Length
SWC-1 x 12	1" FIP x 1" FIP	12"
SWC-1 x 18	1" FIP x 1" FIP	18"
SWC-1 x 24	1" FIP x 1" FIP	24"
SWC-1 x 36	1" FIP x 1" FIP	36"
SWC-1 x 48*	1" FIP x 1" FIP	48"
*48" length Not intended for use on water heaters		



<u>Product Submittal</u>	
Job Name:	_____
Date:	_____
Model#	Quantity: _____
_____	
Architect/Contractor: _____	

