



# 69627 Installation Instructions

## Product Overview:

These Visor-Style Trim Rings recess the headlamp into the housing, and add a traditional "eyebrow" design to the headlamp shell. Classic French Ring design.

## Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes and requires no wiring on most installations.

### Required Tools

- Philips-Head Screwdriver

## Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.



If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at [Support@EagleLights.com](mailto:Support@EagleLights.com).

## Installation:

Below are steps for most typical installations on motorcycles that use 5 ¾" headlights. Steps may be different depending on the year, make, and model of the motorcycle. Please ensure you

2

have read through the instructions and understand them clearly before attempting the installation.

 <b>WARNING!</b> 
<ul style="list-style-type: none"><li>• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.</li></ul>

1. Place a cloth or protective covering over the front fender.
2. Loosen the bolt on the bottom of the new trim ring.
3. Place the new french ring over the existing stock ring.
4. Ensure the ring is secure in place over the groove on the headlight. Red threadlocker can be used on the bolt.