



8700-KV Headlight Installation Instructions

Product Overview:

The 8700C-KV LED headlight kit provides 3X the safety and visibility compared to the stock headlight unit. It is a plug and play LED headlight kit that fits 2009-2021 Voyager and 2011-2021 Vaquero model motorcycles. Each unit is covered by a Lifetime Warranty.

Typical Installation

Normal installation requires only a few tools, takes less than 45 minutes and requires no wiring on most installations.

4mm Hex Key

#2 Phillips Head Screwdriver

8mm Socket



Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

Below are steps for typical installations on Kawasaki models. Steps may be different depending on the model and year of your motorcycle. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

 WARNING! 
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.

Install LED Headlight Into Ring:

- Make sure the three 4mm hex-head spring screws are tightened all the way down into the supplied adapter bracket.
- Remove the three phillip head screws in the installation ring that hold on the front trim piece.
- Put the new LED headlight into the installation ring. There are 3 cut outs on the bracket and 3 standoffs on the light. They need to be matched up for the LED light to sit flush in the mounting bracket.
- Reinstall the front trim piece removed in step one back on with the three shorter M4 screws provided. Do not use the longer screws as those will be needed in a different step.

Remove Stock Headlight

- Using a 4mm hex key, remove the bottom bolt from the chrome front cowl.
- Holding the front cowl on the top, pull it towards you to remove it.
- The stock headlight is held in with three push rings. To remove these, push them in the center and pull them out. They will not be reused and can be put to the side.
- Remove the four mounting bolts with an 8mm socket slowly as the headlight will come out at the same time. Hold the headlight and unplug it from the bike.

Install the LED Headlight

- With the stock headlight removed, plug in the new LED headlight into the motorcycle's headlight harness.
- Place the headlight assembly into the bike and fasten it with the stock 8mm bolts.
- Test the function of the headlight's high and low beam functions. If you run into issues, please contact us via email. Our email address is support@eaglelights.com.
- It is recommended to aim the headlight at this point. The spring screws are already tightened down, so the initial adjustment will only be outwards. Use the directions provided in your owner's manual for detailed instructions on the headlight adjustment.
- After aiming the headlight, install the inner trim piece.
- Reinstall the outer cowl by clipping it in at the top and then use the 4mm bolt from step 1 to fasten it at the bottom.