



# 8900TL-HDA Installation Instructions

## Product Overview:

The Eagle Lights LED tail light for Honda VTX, Shadow, Valkyrie, Sabre, and Aero Models is over 3x brighter than the stock bulb. With a completely plug and play install, it only takes 5 minutes to upgrade your motorcycle to LED.

## Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes.

### Required Tools


- Philips-Head Screwdriver

## Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at [Support@EagleLights.com](mailto:Support@EagleLights.com).

## Installation:

Below are steps for a typical installation. Steps may be different depending on the model. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

 <b>WARNING!</b> 
<ul style="list-style-type: none"><li>• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.</li></ul>

1. Remove the stock lens from the bike. Typically it is two screws holding on the lens. Set lens and screws aside.
2. Remove the stock bulb.
3. If the vertical reflector is present, please remove the reflector from tail light housing. Depending on the model, the reflector will either clip in or have a bolt securing it in place. If a bolt is visible, remove the bolt before attempting to remove the reflector.
4. Clean the area with isopropyl alcohol. Let dry for 5 minutes.
5. If the housing where the reflector has been removed is flat, remove the double sided tape on the back of the unit.

6. Plug in the tail light.
7. Line up the tail light, and place it in the housing.
  - a. On some models the chrome molding piece is not flat. In this case the tape will not be needed. The lens will hold the unit in place on these models.
8. Reinstall the lens.
9. Test the brake and running functions of the unit.