



8900TL6-R-FW

Installation

Instructions

Product Overview:

The 8900TL6 tail light has a built-in flashing brake light to take your safety to the next level. The light connects directly to your Harley Davidson motorcycle and requires no programming or wiring for the flashing brake light function. Once the brake is activated, the light will flash 3 times and then turn a bright red.

Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes and requires no wiring.

Required Tools

- Philips-Head Screwdriver

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

Below are steps for a typical installation on most Harley Davidson models with squareback style tail lights. Steps may be different depending on the model. Please ensure you have read through the instructions and understand them clearly before attempting the installation.



WARNING!



- To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.

1. Remove the stock tail light. It is held in with two screws. Remove and set them aside.
2. Remove the protective covering from the included gasket. Rout the tail light harness through the gasket. Place the gasket on the back side of the light.
3. Connect the tail light to the harness.
4. Reinstall the new LED tail light using the OEM screws.
5. Repeat for the other side.
6. Test brake light function.

If the security light comes on when engaging the brake, please use the following reset procedure:

1. Turn ignition on.
2. Turn on 4 way flashers.
3. Turn ignition off and allow the 4way flashers to flash for about 10 minutes.
4. Turn ignition on.
5. Turn off the 4 way flashers.
6. Turn ignition off.
7. Test the brake light function.