



9500BG2 Instructions.

Product Overview:

Below are steps for a typical installation on most bikes. Steps may be different depending on the model and year of your motorcycle. Ensure you have read through the instructions and understand them clearly before attempting the installation.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

WARNING!	
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.• Wear eye protection.	

1. Remove the fairing. Consult your owners manual if you are unfamiliar with this process. Place the fairing to the side.
2. Install the adjuster on to the light with the provided hardware. Take the two hole bracket. Place the adjuster through one end and bolt it into the light on the other end.



3. Install the provided black retaining clip into fairing



4. Using the provided bolts and washers, connect the headlight to the fairing.



5. Place the fairing trim over the headlight.

6. Optional: Connect the turn signals and running lights.

- a. To connect the left and right turn signals, locate the turn signal wiring underneath the fairing. The wiring color codes are as follows.

Color	Function
Brown	Right Turn Signal Positive
Purple	Left Turn Signal Positive
Red	Running Light Positive

- b. The red wire can be spliced to the extra headlight plug connection.

7. Connect the main headlight plug to the bike's wiring harness.
8. Reinstall the fairing.
9. Test high and low functions of the headlight.