



AFH Installation Instructions

Product Overview:

The Eagle Lights AFH01 Anti-Flicker Harnesses are designed to balance out the current draw of the LED Headlight Conversion kit and offset the warning signals on the dash board. It will also eliminate LED headlight flickering that is caused by the Vehicle's computer not recognizing the low draw LED bulb.

Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes.

Required Tools



- Philips-Head Screwdriver

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

Below are steps for a typical installation on most Harley Davidson models. Steps may be different depending on the model. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

 WARNING! 
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.

1. Lay the harness out in front of the engine. Ensure that the side with the relays is on the same side as the battery.
2. Take the red lead coming from the fuse and connect it to the positive battery terminal.
3. Connect the male ends of the anti-flicker harness into the car's lighting harness.
4. Connect the LED headlights to the yellow ends on the left and right side.

5. Coming off of the yellow plug is a terminal to ground the system. You can use an existing bolt or self tapping screws, but verify you have a good ground.
6. Test the headlights to ensure the harness is installed properly.
7. Route the wiring harness. Keep it away from heat sources and moving parts within the engine compartment.