



BMW LED Headlight Upgrade Instructions.

Product Overview:

Below are steps for a typical installation on most BMW R100R, R100T, R1150R, R1200C R850 Models. Steps may be different depending on the model and year of your motorcycle. Ensure you have read through the instructions and understand them clearly before attempting the installation.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

WARNING!	
	<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.• Wear eye protection.

- **Step 1:** Remove stock headlight and retaining ring. There are either one or two bolts along the bottom of the bucket to remove the headlight.
- **Step 2:** Remove the headlight from the bucket. Unplug and the headlight from the factory wiring harness.
- **Step 3:** Remove the reflector unit from the housing. To do this, remove the clips around the headlight bucket. **Caution: these are under tension! Remove them carefully and set them aside.** Remove the reflector unit from the retaining ring.

2

- **Step 4:** Attach the adapter ring from the kit to the new LED headlight with the provided hardware.
 - Using the L brackets and allen key bolts, attach the ring as shown below.



- The brackets attach with the long side to the base of the light and the bent part toward the gasket.



- The last bracket will be slightly higher than the other and rests on a different part of the headlight casing.

3

- Using the 4 rubber grommets, center the headlight in the ring by placing them in between the ring and the headlight in the gap in the adapter ring.



- **Step 5:** Reinstall the new LED headlight to retain the ring with the stock clips that were set aside in step 3.
- **Step 6:** Plug in the headlight and reinstall the light into the bucket.
- **Step 7:** Test high and low beam functions.