



Challenger™ Installation Instructions

Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes and requires no wiring on most installations.

Required Tools

- Philips-Head Screwdriver
- Flat-Head Screwdriver

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation on Indian Models:

Below are steps for most typical installations on Indian Chieftain models with a 7" headlight and 4.5" passing lights. Steps may be different depending on the model of Chieftain. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

WARNING!



- To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.
- Wear eye protection.



- Remove plastic ring with flat head screwdriver. Pry away from the bike gently. The plastic ring is held in with clips.
- Use a phillips screwdriver to remove the 4 screws around the headlight. Put the screws aside.
- Take off the retaining ring. Put the retaining ring aside.
- Turn the steering wheel all the way to the left.
- Locate the headlight harness. It will have black, yellow and green wires.
- Cut zip ties holding the harness inside the motorcycle.

2

- Disconnect the harness and remove the headlight.
- Connect the new LED headlight to the motorcycle harness.
- Put the retaining harness back on the headlight and screw it in with the screws from step 2.
- Reinstall the plastic ring and test the headlight functions.