



EL60WR-P-UV Installation Instructions

Product Overview:

The Eagle Equalizer eliminates hyper flash when installing LED turn signals on pre-2013 Harleys. It does not produce heat or put a load on the electrical system under use. Only one unit is needed for either 2 or all 4 turn signals.

Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes.

Required Tools

- Philips-Head Screwdriver

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.



WARNING!



- To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.
- Confirm the Ignition Switch is in the OFF position. If not, switch the bike to the off position.
- Remove the seat and locate the OEM rear lighting harness under the seat. This can be identified as it goes underneath the rear fender.
- Using the posi-tap connectors, connect the Eagle Equalizer to the rear lighting harness.
 - Connect Purple wire from Eagle Equalizer to the left rear turn signal circuit.
 - Connect White wire from Eagle Equalizer to the right rear turn signal circuit.
 - Connect Black wire from Eagle Equalizer to the chassis ground circuit.
 - Connect Blue wire from Eagle Equalizer to the 12vdc switched power circuit.
- 5. Turn Ignition Switch to the ON position and test turn signals for proper operation.