



EL60WR-S Installation Instructions

Product Overview:

On some models, a load resistor is needed to prevent the code from being flagged. When the light is on, the motorcycle's computer can no longer "see" the tail light. This load resistor will fix that issue. It does not hurt the bike or the light to leave it the way it is, but if you want to stop the code, it can be fixed by installing the resistor on the rear lighting harness underneath the seat.

Typical Installation



Normal installation requires only a few tools, takes less than 15 minutes.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

Below are steps for a typical installation on most Harley Davidson models. Steps may be different depending on the model. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

	WARNING!	
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.		

How To Install the Load Resistor :

- Locate the rear lighting harness. There may be a silver tag with the words "Rear Lighting Harness" on it. If not, it can be identified as it is the only harness that will go underneath the rear fender.
- Take one end of the resistor and connect it to the ground (typically the black wire) on the harness.
- Take the other end of the resistor and connect it to the brake light positive (typically the red wire with a yellow stripe).
- Mount the resistor away from other wiring. The resistor will get hot during use. We recommend mounting it away from other wiring and fastening it to metal.